WATER WELL RECORD F	orm WWC-5	KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMB		RANGE NUMBER
Sedgwick NE 1/4 SE 1/4 NE Distance and direction from nearest town or city street address of well if located within city?	1/4 11	T 27 S	R 2E E/W
30' N. of Rockhill and 100' West of Center 143rd E., Reserve L Wichita, Kansas			
2 WATER WELL OWNER: RITCHIE DEVELOPMENT			
RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N., Bldg. 1000		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	mber:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 8	- '"	ELEVATION:	
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 55	ft.	ft.	ft.
Burns test data. Wallium		SURFACE MEASURED ON mon ft. after hour	/day/yr: 10/29/08 s of pumping @ gpm
NW NE X			rs of pumping @ gpm
Est. Yield: gpm Well was Some Hole Diameter 12 in.	to 85	ft. and in.	to ft.
WELL WATER TO BE USED AS: SW SE 1. Domestic 3. Feedlot 5. Public wa	ater supply 7. Law	9. Dewater	-
	vater supply 8. Air c		12. Other (Specify below) ing well
S Was a chemical/bacteriological sample submitted to	Department? YES	NO ; If yes,	what mo/day/yr was sample
submitted	Was	s Water Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR)	9. Other (Spec	cify below) CASING JOINTS:	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete	tile SDR-26		Welded Clamped
Blank casing diameter 5 in. to 55 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	uge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. AB\$	11. Other (specify)	- 1-1-1
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
			Tr. None (open nois)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 55 ft. to		From ft.	to ft.
From ft. to	,	From ft.	to ft.
STOTAL TRANSPORT	o 85 ft.,	From ft.	to ft.
L COOLITANTEDINO	o ft.,	From ft. Other hen	to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. to 24 ft., From	3. Benton		ft. to ft.
What is the peacest source of possible contamination:	ft. to	·	
1. Septic tank 4. Lateral lilles	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well 16. Other (specify below)
2. Sewer lines 5. Cess Pool 6. Sewage lagoon 14. Abandon water went			
Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilizer storage	How many feet? 30	ft plus
Direction from well? North	From To		OGIC LOG
0 4 topsoil			
4 15 clay			
15 90 shale 90 97 limestone			
90 97 limestone			
	 		
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and			
was completed on (mo/day/year) 10-29-2008 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10-31-2008			
under the business name of Harp Well and Pump Service by (signature) Todd S. Howb			