			WATER	WELL RE	CORD	Form W	WC-5	KSA 82a-12	212		
1'1	ON OF WATE		FRACTION	CXX			CTION NUMB		HIP NUMBER	RANGE N	
	wick	<i>N</i> W		/4 SW	1/4 NE	1/4	11	Т	27 s	R 21	E/W
1		m nearest town or city s ked Pine			-						
	ER WELL		NKE, Todo	'ichita, Ka 1	11545						
									Board of Agri	culture, Division of V	Water Resource
RR#,ST. ADDRESS,BOX #: 1917 N. Crooked Pine CITY, STATE: Wichita, Kansas ZIP CODE: Application in										nher:	
3 1004	TE WELL'S LO			MPLETED WE	11. 1	.00 ft		ELEVATION:		iber.	
	AN "X" IN SEC	CTION BOX:		ater Encounter			ft.		ft,		ft.
	N I		•	WATER LEVE				SUBEACE MEAS		lav/yr: 1/14	
	-NW			Pump test data		ater was	OW LAND S	ft. after	SURED ON mo/d	of pumping @	•/∪∋ gpr
la l	```` >	VE	Est. Yield:	gpm		ater was		ft, after		of pumping @	gpn
w Mile		E Bo	re Hole Diame	<u> </u>	in.		100	ft. and	in.	to	ft,
-			LL WATER TO	BE USED AS					9. Dewateri	ng 11. Inje	ction well
111	- SW -	1	Domestic	3. Feedlot				and garden on		12. Other (S	pecify below
			Irrigation	4. Industrial			ly 8. Air co		10. Monitorin	ig well vhat mo/day/yr v	vae eamole
	S		as a chemical/ba mitted	cteriological sam	pie submitted to	Department?		Water Well Disi			NO
5 TY	PE OF CAS	ING USED:	5 144		7. Fib	- 0	Other (Speci		SING JOINTS: (Glued	Threaded
	1. Steel	3. RPM (SR)	5. Wroug	gnt Iron	7. Fiberglas	•		ily below) OF	01140 3011413.	Welded	Clamped
	2. PVC	> 4. ABS	6. Asbes	tos-Cement	8. Concrete	tile S1	OR-26				Olampou
Blank cas	sing diamete	er 5 i	n. to	28 ft.,	Dia.	in.	to	ft.,	Dia. i	in. to	ft.
Casing h	neight above	land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or gaug	e No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Stee	_	. Stainless Steel	Fibergla	ss C	7. PVC	9.	ABS	11. C	other (specify)		
2. Bra	ss 4	. Galvanized	6. Concrete	e Tile	8. RMP (SR)	10.	Asbestos-Ce	ement 12. N	lone used (open	hole)	
SCREEN	OR PERFO	RATION OPENING	- · · · -								
1. Conti	inuous slot	3. Mill slo	t :	5. Gauzed wra	pped	7. T	orch cut	9. Dr i	iled holes	11. None (c	pen hole)
2. Louve	ered shutte	r 4. Key pui	nched 6	6. Wire wrapp	ed	(8. S	aw cut	10. Ot	her (specify)		
SCREEN	- PERFORA	TION INTERVAL	From	28 f	ft. t	o 100	ft.,	From	ft.	to	ft.
			From			0	ft.,	From	ft.		ft.
G	RAVEL PA	CK INTERVALS:	From			to 100	ft.,	From	ft.	to	
1			From			to				to	ft.
C CPO	UT MATERI	A1 C:				-	ft.,	From	ft.	to	ft.
<u> </u>	Intervals:	From 4			nt Grout		3. Bentonit	-		onite hole plu	•
t		eurce of possible con		o 24 ft	., From	ff	. to	ft.,	From	ft. to	ft.
								15. Oil well/G	Sas well		
2. Sewe	r lines	5. Cess Po	ool	8. Sewage la	goon	11. Fuel st	orage	14. Aban	don water well	16. Other (sp	ecify below)
3. Water	rtight sewe	r line 6. Seepage	e pit	9. Feed yard		12. Fertiliz	er storage				
	from well?	East						How n	nany feet? 40 f	t. plus	
From	То	L	ITHOLOG	IC LOG		From	То		LITHOLO	GIC LOG	
<u> </u>	4	topsoil								.,	
15	15 70	clay shale				-	 	 			
70	100	limestone				+	+		******		
	100	THE STORE				<u> </u>		1	2730		
							-				
								<u> </u>			**
				· · · · · · · · · · · · · · · · · · ·			 				
							1				

						4					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and											
was completed on (mo/day/year) 1/14/2009 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/19/2009											
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp											