WATER V	VELL RECORD F	orm WV	/C-5 K	SA 82a-121	2				
1 LOCATION OF WATER WELL: FRACTION	l l			SECTION NUMBER TOWNSHIP NUM					
Sedgwick NE 1/-		1/4	1	т 27	S	R	2E	E/W	
Distance and direction from nearest town or city street address of w 15405 E. 24th St. No. Wie	chita, Kansas								
2 WATER WELL OWNER: PORTER HOM									
RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N. Bldg. 600									
CITY, STATE: Wichita, Kansas		ZII	P CODE:		Application Nun	nber:			
3 LOCATE WELL'S LOCATION 4 DEPTH OF COM	IPLETED WELL: 11	.2 ft.		ELEVATION:			-		
WITH AN "X" IN SECTION BOX: N Depth of groundwar	er Encountered:	ft.			ft.			ft.	
WELL'S STATIC V	ATER LEVEL 50	FT. BELO	W LAND SU	RFACE MEASU	RED ON mo/o	lay/yr: 2	2/16/0	19	
''' ''-	ump test data: Well wa	ter was		ft. after	hours	of pumping (<u>D</u>	gpm	
Est. Yield: Bore Hole Diamet	gpm Well wa er 12 in.	ter was to 1	12 4	ft. after		of pumping (-	gpm	
≥ W Bore Hole Diamet		to 1	.12 ft.	and	in.	11	-	ft. on well	
		ter supply	7. Lawn a	nd garden only	> Dewateri	··9	-	cify below)	
2. Irrigation	4. Industrial 6. Oil field w	ater supply	8. Air con	ditioning	10. Monitorin	ng well test	well		
S Was a chemical/bac submitted	teriological sample submitted to I	Department?	YES	NO Vater Well Disinfo		what mo/day/	yr was NO		
5 TYPE OF CASING USED: 5 Wroug		0.04			ING JOINTS: (Glued		hreaded	
1. Steel 3. RPM (SR) 5. Wroug	ht Iron 7. Fiberglass		ther (Specify	below) CAS	ING JUIN 15: V	Welded		Clamped	
2. PVC 4. ABS 6. Asbest	os-Cement 8. Concrete t	ile SDI	R-26			,,,,,,,,,		Jampou	
Blank casing diameter 5 in. to	52 ft., Dia.	in.	to	ft., I	Dia.	in. to		ft.	
Casing height above land surface: 12 in.,	Weight:	2.35 lb	os. / ft.	Wall thi	ckness or gauç	ge No2	214		
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete	Tile 8. RMP (SR)	10. A	sbestos-Cen	nent 12. No	ne used (open	noie)			
SCREEN OR PERFORATION OPENINGS ARE:	Courad washing	7 To		O Deille	ed holes	11 Non	o (one	en hole)	
	. Gauzed wrapped		rch cut			11. 14011	e (ope	en note)	
2. Louvered shutter 4. Key punched 6	. Wire wrapped	_	w cut	10. Otne	r (specify)				
SCREEN - PERFORATION INTERVAL From	52 ft. to	112	ft.,	From	ft.	to		ft.	
From	ft. to		ft.,	From	ft.	to		ft.	
GRAVEL PACK INTERVALS: From	24 ft. to	112	ft.,	From	ft.	to		ft.	
From	ft. to)	ft.,	From	ft.	to		ft.	
GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3	B. Bentonite		Other bent	onite hole	plug	;	
Grout Intervals: From 4 ft. to	o 24 ft., From	ft.	to	ft.,	From	ft.	to	ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy			k pens	13. Insection	3. Insecticide storage 15. Oil well/Gas well				
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							ify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? South		· p		How ma	ny feet? 10 t				
From To LITHOLOG	IC LOG	From	То		LITHOLO	GIC LOC	}		
0 4 topsoil 4 18 clay		+	 						
4 18 clay 18 112 shale		1			- "				
A									
		-							
		1							
							_		
							-		
7 Contractor's or Landowner's Certification: This wat	er well was 1. constructed	2. re	constructed	I or 3. I	olugged	under my juri	sdiction	n and	
was completed on (mo/day/year) 2/16/2009 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/18/2009									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb									