WATER WELL RECORD FO	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NW 1/4 SE 1/4 SW	1/4 2	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city? 2314 N. Rosemont Ct. Wichita, Kansas			
2 WATER WELL OWNER: SPROUL CONSTRUCTION			
RR#,ST. ADDRESS,BOX #: 3500 N. Ridge Road Building 1000		Board of Agr	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nur	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 90	ft.	ELEVATION:	
Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 20		RFACE MEASURED ON mo/	day/yr: 4/22/09
NW NE Pump test data: Well water			s of pumping @ gpm
Est. Yield: gpm Well water Spm Well	er was to 90 ft.	ft. after hours	s of pumping @ gpm to ft.
₩ELL WATER TO BE USED AS:		9 Dewater	44 1-141
	er supply 🤙 Lawn a	nd garden only	12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field wa	ater supply 8. Air con	16	ng well what_mo/day/yr_was sample
S Was a chemical/bacteriological sample submitted to D submitted		(NO) ; If yes, vater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR) Welded Clamped			
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete till	9		
Blank casing diameter 5 in. to 30 ft., Dia.	in. to	ft., Dia.	in. to ft.
	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 30 ft. to	90 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	90 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite		tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
1. Septic tank 4. Lateral lines 9. Sowage larger 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
2. Sewer lines 5. Cess Pool 6. Southern the second of the			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1 Direction from well? West	z. i orunzor otorago	How many feet? 10	ft. plus
From To LITHOLOGIC LOG	From To	<u> </u>	OGIC LOG
0 3 topsoil			4. W
3 15 clay 15 90 grey shale			
15 90 grey shale			
Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and			
was completed on (mo/day/year) 4/22/2009 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/27/2009			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp			