WATER WELL RECORD Form WWC-5 KSA 82a-1212										
	LOCATION OF WATER WELL: FRACTION					TION NUMBER	1	IIP NUMBER	RANGE NUMBER	
Sedgwick		SE 1/4		1/4 NV	1/4	11	T :	27 s	R 2	E E/W
Distance and direction from nearest town or city street address of well if located within city? 2018 N. Crooked Pine St. Wichita, Kansas										
2 WATER WELL OWNER: ROBL CONSTRUCTION										
RR#,ST. ADDRESS,	Rearret of Agricultura, Division of Water Pageur									Water Resource
CITY,	STATE: Wich	nita, Kansas			Z	IP CODE:		Application Nur	nber:	
3 LOCATE WELL'S LO	CATION 4	DEPTH OF COM	IPLETED W	/ELL:	97 ft.		ELEVATION:			
WITH AN "X" IN SEC	Dep	pth of groundwat	ter Encounte	ered:	f	ł.		ft.		ft.
	W	ELL'S STATIC W	VATER LEV	EL 30	FT. BELO	OW LAND SU	JRFACE MEAS	SURED ON mo/o	day/yr: 4/	8/09
NW Z	- NE		ump test da		vater was		ft. after	hours	s of pumping @	gpm
M Mile		Est. Yield:	gpm er 12	•	vater was	07 6	ft. after		s of pumping @	gpm
	' ! !	ore Hole Diamet			to	9 7 ft.	and	in.	to	ft.
sw -	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below									
	2	2. Irrigation	4. Industria	6. Oil field	water suppl	y 8. Air cor	ditioning	10. Monitorii	ng well	
S		Vas a chemical/bac bmitted	teriological sa	mple submitted t	o Department?	YES	NO Vater Well Disi		what mo/day/yr	was sample NO
5 TYPE OF CAS		Diffitted							\geq	
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) Welded Clamped										
2. PVC	> 4. ABS	6. Asbest	os-Cement	8. Concrete	e tile SD	R-26				Olampou
Blank casing diamete	er 5	in. to	37 ft.	, Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above	land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or gau	ge No21	4
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)										
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)										
				•	0.5					
SCREEN - PERFORA	TION INTERVAL	From	37	ft.	to 97	ft.,	From	ft.	to	ft.
65A) (E) BA	OK INTERVALC:	From	24	ft. ft.	to 97	ft.,	From	ft.	to	ft.
GRAVEL PAG	CK INTERVALS:	From	24			ft.,	From	ft.	to	ft.
- 05017 147551	41.0	From	·	ft.	to	ft.,	From	ft.	to	ft.
GROUT MATERIA	1. 11041	cement ft. to		nent Grout		3. Bentonite			tonite hole p	_
What is the nearest so	110111			ft., From			ft.,	From		o ft.
1. Septic tank	4. Lateral	l lines	7. Pit privy	'	10. Livesto		13. Inse c	ticide storage	15. Oil well	
2. Sewer lines	5. Cess F	ool	8. Sewage	lagoon	11. Fuel sto	-	14. Aban	don water well	16. Other (specify below)
3. Watertight sewe	r line 6. Seepa	ge pit	9. Feed ya	rd	12. Fertilize	er storage		10	C41	
Direction from well? From To	East	LITHOLOG	IC L OG		From	То	How r	nany feet? 10	OGIC LOG	
From To	topsoil	LITHOLOG	IC LOG		FIOIII	10		LITHOLC	JGIC LOG	
4 15	clay									
15 75	shale									741 - 44
75 97	limestone					1				
										H-V
						+				
							V4.11			
									····	
					-					
7 Contractor 1	andowneds Cartis	cotion: This	or well	1		Nonetweet :	1 05 0	pluggod	under my insigal	iction and
\vdash	andowner's Certifi	cation: This wate 4/8/2009				econstructed		plugged	under my jurisd	ction and
was completed on (,			-	knowledge and		1/2000	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/10/2009										
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb										