WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NW 1/4 SW 1/4 SE	1/4 2	T 27 S	R <b>2E</b> E/W
Distance and direction from nearest town or city street address of well if located within city?   13603 Ayesbury Wichita, Kansas			
2 WATER WELL OWNER: NIES CONSTRUCTION			
RR#,ST. ADDRESS,BOX #: 10333 E. 21st St. N. #303		Board of Agri	culture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nun	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 97		ELEVATION:	
WITH AN "X" IN SECTION BOX:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 45		JRFACE MEASURED ON mo/o	
			of pumping @ gpm
			s of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	to <b>97</b> ft.		to ft.
← WELL WATER TO BE USED AS:		9. Dewateri	ng 11. Injection well
1. Domestic 3. Feedlot 5. Public wat	er supply 7. Lawn a	and garden only	12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field wa			•
S Was a chemical/bacteriological sample submitted to D submitted		Vater Well Disinfected?	what mo/day/yr was sample
			Glued Threaded
5. 5. Wrought Iron 7. Fiberglass   1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS: (	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete til	e 50R-26		olamped
Blank casing diameter 5 in. to 47 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gaug	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:		0	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer	ment 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
····			
SCREEN - PERFORATION INTERVAL From 47 ft. to	<b>97</b> ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	<b>97</b> ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
1. Septic tank 4. Lateral lines			
2. Sewer lines 5. Cess Pool 6. Contage lagoon 4.1 as of oronge 14. Abandon water went			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? South	Trong To	How many feet? 10	
From To LITHOLOGIC LOG	From To	LITHOLC	OGIC LOG
0 4 topsoil 4 15 clay			
15 80 shale			
80 97 shale and limestone			
			·····
7 Contractor's or Landowner's Certification: This water well was 1. constructed	) 2. reconstructed	d or 3. plugged	under my jurisdiction and
	2. reconstructed		under my jurisdiction and
was completed on (mo/day/year) 5/19/2009 and this record in		knowledge and belief.	under my jurisdiction and
was completed on (mo/day/year) 5/19/2009 and this record in	s true to the best of my	knowledge and belief.	-2009