			WATER	R WELL RE	CORD	Form WV	VC-5 K	SA 82a-12	12		
1 LOCATION		R WELL:	FRACTION	CXX	~~	- 1	TION NUMBER	1	IP NUMBER	RANGE N	
Sedgw			SW	1/4 SW	1/4 SE	1/4	2		27 s	R 21	E E/W
Distance and direction from nearest town or city street address of well if located within city? 2215 N. Loch Lomond Wichita, Kansas											
2 WATER WELL OWNER: PORTER, Mario Homes, Inc.											
RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N. Bldg. 600											
	CITY,	STATE: W	ichita, Kans	as			P CODE: 6	7226	Application Num	ber:	
	WELL'S LO		4 DEPTH OF C	OMPLETED W	ELL: 9	7 ft.		ELEVATION:			
WITHAN	"X" IN SEC	HON BOX:	Depth of ground	water Encounte	red:	ft.			ft.		ft.
		1	WELL'S STATI	C WATER LEVE	L 30	FT. BELO	W LAND SU	JRFACE MEAS	URED ON mo/d	lay/yr: 12/'	7/09
	w} -	-NE		Pump test dat				ft. after		of pumping @	gpm
w Wile		' ₋	Est. Yield:	gpm meter 12		ater was to 9	7 4	ft. after		of pumping @	gpm
₹ w			Bore Hole Dia	TO BE USED A		10 5)7 ft.	and	in.	to 11 Inje	ft. ection well
1 1	w	-SE	1. Domestic	3. Feedlot		ater supply	7. Lawn a	ınd garden on	9. Dewaterir	'y	pecify below)
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted was Water Well Disinfected? YES NO											was sample NO
	Steel	3. RPM	5. Wro	ought Iron	7. Fiberglass	•	ther (Specify	below) CA	SING JUINTS: (Welded	Threaded Clamped
2.1	PVC	4. ABS	6. Ast	estos-Cement	8. Concrete	tile SD	R-26				5.ap55
Blank casing	g diamete	r 5	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia. i	n. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)											open note,
2. Louvere	ed shutte	r 4. Ke	ey punched	6. Wire wrap	pea	_	w cut	10. Ott	ner (specify)		
SCREEN - P	ERFORA	TION INTERV	AL From	40	ft. to	97	ft.,	From	ft.	to	ft.
			From	2.5	ft. to		ft.,	From	ft.	to	ft.
GRA	AVEL PAC	CK INTERVAL	S: From			o 97	ft.,	From	ft.	to	ft.
<u></u>			From		ft. t	0	ft.,	From	ft.	to	ft.
6 GROUT	6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout									onite hole pl	•
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From 3 ft. to 16									16 ft.		
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Liv							k pens	13. Insecticide storage 15. Oil well/Gas well			
2. Sewer I		5. Ce	ss Pool	8. Sewage I	agoon	11. Fuel sto	rage	14. Abane	don water well	16. Other (s	pecify below)
3. Waterti		r line 6. Se	epage pit	9. Feed yar	d	12. Fertilize	r storage				
Direction fro	-	West						How m	nany feet? 10 f		
From	To		LITHOLO	OGIC LOG		From	То		LITHOLO	GIC LOG	
0		topsoil				 					
12	12 65	clay brown sha	nle			1			···		
65		grey shale							~ ~ ~ ~		
		-							RECEIVE	:D	
1									DE0 01 0	000	
									DEC 21 2	009	
		BUREAU OF WATER									
								DUK	EAU OF I	WAIEN	
							 				
											
7 Contra	ctor's or L	andowner's C	ertification: This	water well was 1	constructe	d) 2. re	constructe	d or 3.	plugged	under my jurisdic	tion and
was completed on (mo/day/year) 12/07/2009 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/10/2009											
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp											,