


Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: Sedgwick NW ¼ NW ¼ SE ¼		1		T 27S S		R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 2531 N RIDGEHUURST		Global Positioning System (decimal degrees, min. of 4 digits)					
2 WATER WELL OWNER: RR#, St. Address, Box # : SHARP HOMES City, State, ZIP Code : WICHITA, KS.		Latitude: Longitude: Elevation: Datum: Data Collection Method:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 110 ft.					
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 36 ft. below land surface measured on mo/day/yr 6/30/09 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 25 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial X Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr Sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) X PVC 4 ABS 7 Fiberglass		CASING JOINTS: Glued X Clamped Welded Threaded					
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 14 in., Weight 2.4 lbs./ft. Wall thickness or gauge No. 160PSI							
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass X PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot X Mill slot 5 Gauge wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 60 ft. to 110 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 38 ft. to 110 ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite 4 Other							
Grout Intervals From 38 ft. to 3 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well X Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well							
Direction from well? NORTHEAST How many feet? 15							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 3 Top soil							
3 27 Clay							
27 64 Limestone							
64 105 Blue Shale							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/14/09 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 740 This Water Well Record was completed on (mo/day/year) 8/10/09 under the business name of Weninger Drilling Inc by (signature)							
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.							