WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 SW Sedgwick SE 1 27 2E 1/4 1/4 T S R F/W Distance and direction from nearest town or city street address of well if located within city? 15406 E. Camden Chase Ct. Wichita, Kansas WATER WELL OWNER: NAGY, Melissa Board of Agriculture, Division of Water Resource RR#.ST. ADDRESS.BOX #: 15406 E. Camden Chase Ct. ZIP CODE: 67228 Wichita, Kansas CITY, STATE: 98 ELEVATION: 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered ft. WELL'S STATIC WATER LEVEL 35 3/30/10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ apm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm to 98 ≌ Bore Hole Diameter 12 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES Was Water Well Disinfected? submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 38 ft. Blank casing diameter to ft.. Dia. ft. Dia in to to Casing height above land surface: 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3. Stainless Steel 5. Fiberglass 1. Steel 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 38 98 ft. ft.. From From to ft. ft. ft From to From fŧ ft GRAVEL PACK INTERVALS: 24 ft. 98 ft From ft... From to ft. From ft. to ft., From ft. Other bentonite hole plug **GROUT MATERIALS:** 6 2. Cement Grout 1 Neat cement 3. Bentonite Grout Intervals: 4 ft 24 ft. From ft. to What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5 Cess Pool 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From To From Τo 0 3 topsoil 3 32 clay 32 68 brown shale 68 98 grey shale plugged under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or was completed on (mo/day/year) 3/30/2010 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 4/2/2010 Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb