	WATER WELL	RECORD F	orm WW	C-5 K	SA 82a-1212	2		
1 LOCATION OF WATER WELL:	FRACTION		SECT	ION NUMBER	1		RANGE NUMI	BER
Sedgwick	SE 1/4 S		1/4	4	T 27	S	R 2E	E/W
Distance and direction from nearest tow	n or city street address of well if loca	•						
10226 E. 26th N.	IZEV CONCEDITORIO	Wichita, Kan	isas					
	KEY CONSTRUCTION	JN				Board of Agri	culture, Division of Wate	r Resource
RR#,ST. ADDRESS,BOX #:	741 W. 2nd Wichita, Kansas					A		
CITY, STATE:				CODE:		Application Nun	nber:	
UCCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETE	D WELL: 60			ELEVATION:			
N.	Depth of groundwater Enco		ft.			ft.		ft.
	WELL'S STATIC WATER			W LAND SU	RFACE MEASUF	RED ON mo/o	day/yr: 6/29/1	0
NWNE	Pump te	st data: Well wat	er was		ft. after		of pumping @	gpm
w Wigh	· 1	pm Well wat		Λ.	ft. after		of pumping @	gpm
1	Bore Hole Diameter	12 in.	to 6 6	U ft.	and	in.	to	ft.
swse	WELL WATER TO BE US 1. Domestic 3. Feed		ter supply <	7. Lawn a	nd garden only	9. Dewateri >	•	
	2. Irrigation 4. Indu					10. Monitorin	12. Other (Specing well	ity below)
	Was a chemical/bacteriologic			YES	(NO)		what mo/day/yr was	sample
	submitted				ater Well Disinfe	cted?	YES NO	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Otl	her (Specify	below) CASII	NG JOINTS: (Glued Ti	readed
	PM (SR)	<u>•</u>	SDR	2-26			Welded C	lamped
2. PVC 4. A		nent 8. Concrete ti	le SD1	. 20				
Blank casing diameter	5 in. to 25	ft., Dia.	in.	to	ft., D	ia.	in. to	ft.
Casing height above land surfac	e: 12 in.,	Weight:	2.35 lb	s. / ft.	Wall thic	kness or gaug	ge No214	
TYPE OF SCREEN OR PERFOR	RATION MATERIAL:							
1. Steel 3. Stainless 5	Steel 5. Fiberglass	7. PVC	9. AE	BS	11. Othe	er (specify)		
2. Brass 4. Galvanized	d 6. Concrete Tile	8. RMP (SR)	10. As	bestos-Cen	nent 12. Non	e used (open	hole)	
SCREEN OR PERFORATION OF	PENINGS ARE:							
1. Continuous slot 3.	Mill slot 5. Gauze	ed wrapped	7. Tor	ch cut	9. Drille	d holes	11. None (ope	n hole)
2. Louvered shutter 4.	Key punched 6. Wire	wrapped	8. Sav	v cut	10. Other	(specify)		
SCREEN - PERFORATION INTER		5 ft. to	60		F			
SCREEN - PERFORATION INTE				ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERV	ALS: From Z	4 ft. to	60	ft.,	From	ft.	to	ft.
	From	ft. to	•	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1	. Neat cement 2.	Cement Grout	3.	Bentonite	C	Other bent	onite hole plug	
Grout Intervals: From	4 ft. to 24	ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of pos		nrivy 1	0. Livestock	pens	13 Insectic	ide storane	15. Oil well/Gas	well
1. Septic tank 4. Lateral lines 4. Cause I have been septimized as the septimization of the s						16. Other (spec		
	0000 / 00/			_	14. Abando	n water well	тогошин (орос	,,
T 43	Seepage pit 9. Fee	d yard 1	2. Fertilizer	storage		10.4	F4	
		<u> </u>	Т г от Т	т. Т	How man	y feet? 10 f		
From To	LITHOLOGIC LO	<u> </u>	From	To		LITHOLC	GIC LOG	
0 4 topsoil 4 15 clay								
15 60 shale								
THE THE PERSON NAMED IN TH								
					·			
			 					
 								
			1 1	- +				
			<u> </u>					
						<u> </u>		
7 Contractor's or Landowner's	Certification: This water well v	vas 1. constructed) 2 rec	constructed	or 3. p	ugged	under my jurisdiction	and
	Certification: This water well v			constructed			under my jurisdiction	and
was completed on (mo/day/yea	er) 6/29/2010	and this record i	is true to the	best of my l	knowledge and be	elief.	•	and
	er) 6/29/2010	and this record i	is true to the	best of my l		elief.	under my jurisdiction	and