	WATER WELL RE	CORD F	orm WW	C-5 K	SA 82a-1212	<u>.</u>			
1 LOCATION OF WATER WELL:	FRACTION	· · · NIE	1	ION NUMBER	1		RANGE NUM		
Sedgwick Distance and direction from nearest town or city	NW 1/4 NW	1/4 NE	1/4	11	Т 27	S	R 2E	E/W	
2021 N. Clearcreek Ct. Wichita, Kansas									
2 WATER WELL OWNER: MANDANIS, Hannah									
RR#,ST. ADDRESS,BOX #: 2021		Board of Agriculture, Division of Water Resource							
	hita, Kansas	FIL: 96		CODE:		Application Num	iber:		
WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED W				ELEVATION:				
 	epth of groundwater Encounte /ELL'S STATIC WATER LEVE	40	ft.	WI WID SH	RFACE MEASUR	ft.	lav/vr: 7/8/1	ft.	
NW	Pump test da			W LAND SU	ft. after		of pumping @	gpm	
1 1 1 1 1	Est. Yield: gpm	Well water			ft. after		of pumping @	gpm	
	Bore Hole Diameter 12	in.	to 9	5 ft.	and	in.	to	ft.	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	/ELL WATER TO BE USED A 1. Domestic 3. Feedlot		er sunniv	7. Lawn a	nd garden only	9. Dewaterii	•		
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
, •	Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample								
	ubmitted						=		
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded Clamped									
2. PVC 4. ABS	Asbestos-Cement	8. Concrete tile	, SDF	(-26				J.a.mpou	
Blank casing diameter 5	in. to 45 ft.,	, Dia.	in.	to	ft., D	a . i	in. to	ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)									
2. Louvered shutter 4. Key p	ounched 6. Wire wrap	ped	8. Sav	v cut	10. Other	(specify)			
SCREEN - PERFORATION INTERVAL	From 45	ft. to	96	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 24	ft. to	96	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout				Bentonite	C	ther bent	onite hole plug	3	
Grout Intervals: From 4 ft. to 24 ft., From			ft.	to	ft.,	From	ft. to	ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy			. Livestoci	k pens	13. Insectici	13. Insecticide storage 15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)							cify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? West	LITUOLOGIO LOG		F			y feet? 10 f			
From To 0 3 topsoil	LITHOLOGIC LOG		From	То		LITHOLO	GIC LOG		
0 3 topsoil 3 15 clay									
15 52 brown shale									
52 96 grey shale									
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 7/8/2010 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/9/2010									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									