WATER WE	LL RE	CORD	Forn	a WWC-5	Di			urces; App. No.		
1 LOCATION County:	OF WA	TER WELL: wick	Fraction /	VW SWNE	5E 9W ¼	Section N	umber	Township Number T 27S S	Range Number R 2E E/W	
County: sedgwick AE 4 WE 4 SW 4  Distance and direction from nearest town or city street address of well if located within city? 2502 N Flutter circle Wichita, Ks.							Global Positioning System (decimal degrees, min. of 4 digits) Latitude: Longitude:			
2 WATER WELL OWNER: Zhent Ong RR#, St. Address, Box # : 2502 n Flutter circle City, State, ZIP Code : Wichita, Ks.						Datum: Data Collection Method:				
3 LOCATE WELL'S LOCATON         4 DEPTH OF COMPLETED WELL 120 ft.         ft.           WITH AN "X" IN         Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.         ft. 2 ft. 3 ft.										
WITH AN ") SECTION BO	OX:	WELL'S STAT	FIC WATE	R LEVEL Well water	60 1	t. below la ft.	ınd surfa . after	ce measured on mo/d hours pump	lay/yr <b>8-1-2010</b> ing gpm	
Est. Yield 18 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial X) omestic (lawn & garden) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs										
S	<b></b>	Sample was sub	omitted				Water W	ell Disinfected? Yes	X No	
5 TYPE OF CA 1 Steel 2 PVC <b>X</b>	ASING 3 R 4 A	USED: 5 LMP (SR) 6 LBS 7	Wrought Ir Asbestos-C Fiberglass	ement 9	Other	ete tile (specify be	CASI elow)	NG JOINTS: Glued Welde Threac	X Clamped ded	
Blank casing diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.  Casing height above land surface 12 in., Weight 2.4 lbs./ft. Wall thickness or gauge No. 160PSI  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC X 9 ABS 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot <b>X</b> 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)  2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 60 ft. to 120 ft. From ft. to ft. From ft. to ft. From ft. to ft.										
GRAVEL PACK INTERVALS: From 60 ft. to 120 ft. From ft. to  From ft. to ft. From ft. to								o ft. o ft.		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout X Bentonite 4 Other Grout Intervals From 2 ft. to 60 ft. From ft. to ft. From ft. to ft.										
Grout Intervals From 2 ft. to 60 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify										
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below)										
X 3 Watertight sewer lines 6 Seepage pit 9 Feedyard  Direction from well? East  12 Fertilizer storage 15 Oil well/ gas well  How many feet? 15										
FROM TO		LITHOL	OGIC LOC	3	FROM	ТО		PLUGGING INTE	ERVALS	
0 3	top									
3 33 33 60		wn clay ken limestone				-				
60 120		e shale								
		70.								
7 CONTRACTO under my jurisdiction				8-1-2010		and this	record is	nstructed, (2) reconstructed true to the best of my k	nowledge and belief.	
Kansas Water Well Contractor's License No. 740 This Water Well Record was completed on (mo/day/year) 9-1-20-10 under the business name of Weninger Drilling inc by (signature) by (signature)										