WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION RANGE NUMBER Sedgwick \mathbf{SW} NE SE 1/4 3 27 S 2E F/W Distance and direction from nearest town or city street address of well if located within city? 2449 N. Woodridge Ct. Wichita, Kansas DONDLINGER, Tom WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2449 N. Woodridge Ct. CITY, STATE: Wichita, Kansas Application Number: ZIP CODE 95 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION **ELEVATION:** WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 50 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was Pump test data: ft. after hours of pumping @ gpm NE ΝW Est. Yield: Well water was ft. after hours of pumping @ gpm apm ≌ Bore Hole Diameter 12 to 95 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 40 Dia. ft... Dia. ft in. tο ft.. in to in. to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9 Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 40 95 ft. to ft. From From ft. ft. From ft. to ft From ft ft. 24 ft. **GRAVEL PACK INTERVALS:** 95 ft. ft... From From to ft. ft. From to ft.. From ft. GROUT MATERIALS: Other 2. Cement Grout bentonite hole plug 3. Bentonite 1. Neat cement Grout Intervals: From 4 ft. 24 ft.. From ft to From ft. What is the nearest source of possible contamination: 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 7. Pit privy 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit West How many feet? 10 ft. plus Direction from well? From LITHOLOGIC LOG From To LITHOLOGIC LOG Tο 0 topsoil 3 8 clay 90 8 gray shale 90 95 limestone

was completed on (mo/day/year) 10/8/2010

Kansas Water Well Contractor's License No. 236

and this record is true to the best of my knowledge and belief

This water well record was completed on (mo/day/year) 10/11/2010

under the business name of Harp Well and Pump Service

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed

by (signature)

Todd S. Harp

plugged

under my jurisdiction and