1 LOCATION OF WATER WELL:	FRACTION				SE	CTION NUMBER	TOWNSHIP		RANGE NU	MBER
☐ Sedgwick	NW 1/4	NE	1/4	SE	1/4	8	т 27	S	R 2E	E/W
Distance and direction from nearest town or city st	reet address of we	II if located	within city							
1709 N. Barrier Cove Ct. Wichita, Kansas										
2 WATER WELL OWNER: MC COLLUM CONSTRUCTION, INC.  Board of Agriculture, Division of Water Resource										
RR#,ST. ADDRESS,BOX #: 518 St	tate St.							Board of Agri	culture, Division of W	ater Resource
CITY, STATE: Augus	sta, Kansas					ZIP CODE:		Application Num	nber:	
	EPTH OF COM	PLETED V	VELL:	80	) f	t.	ELEVATION:			
WITH AN "X" IN SECTION BOX:	h of groundwate	r Encount	ered:			ft.		ft.		ft.
	LL'S STATIC W			15	FT. BEI	LOW LAND SU	RFACE MEASU	RED ON mo/o	day/yr: 12/8	/10
		ımp test d		Well water			ft. after		of pumping @	gpm
	Est. Yield:	gpm		Well wat			ft. after		s of pumping @	gpm
₩ K Bo	re Hole Diamete	- 4	2 in.			<b>80</b> ft.	and	in.	to	ft.
	LL WATER TO	3E USED	AS:					9. Dewateri	ng 11. Injec	tion well
1. SW	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)									
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well  Was a chamical/bacteriological sample submitted to Department? VES NO ; If yes, what mo/day/yr was sample									
	as a chemical/bacte mitted	eriological s	ample sub	bmitted to D	Department		/ater Well Disinf			as sample IO
	matted								$\sim$	
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR)	5. Wrough	t Iron	7. F	iberglass		Other (Specify	below) CAS	ING JOINTS: (		Threaded
2. PVC 4. ABS	6. Asbesto	s-Cement	t 8. C	Concrete til	le S.	DR-26			Welded	Clamped
	n. to		t.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
	10	<b>2</b> 5 1	,							
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11. Other (specify)										
1. Steel 3. Stainless Steel	Fiberglass     Concrete				_			, ,	hole)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot 3. Mill slo	r 5.	Gauzed v	wrapped	נ		Torch cut		ed holes	11. None ( o	heu uoie)
2. Louvered shutter 4. Key pu	nched 6.	Wire wra	pped		8.	Saw cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVAL	From	25	ft.	to	80	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24	ft.	to			From	ft.	to	ft.
STATEL FACT INTERVALS.		4-1				,				
	From		ft.	to	,	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat c			ment G			3. Bentonite		Other bent	tonite hole plu	•
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									ft.	
What is the nearest source of possible co		7. Pit priv	y	1	0. Lives	tock pens	13. Insecti	cide storage	15. Oil well/G	as well
1. Septic tank 4. Lateral	illes	•	•		11. Fuel :	•		•	40.04	
2. Sewer lines 5. Cess Footi										
3 Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? Southwest How many feet? 20 ft. plus										
Bir Cottor: It Cit.	_ITHOLOG	CLOG	:		Fror	m To	FIOW ITE		OGIC LOG	
	LITHOLOG	C LOC			17101	" 10		LITTOL	JOIC LOG	
0 3 topsoil 3 15 clay										
15 80 grev shale										
TO THE STATE OF TH										
					-					
					+					
					-					
					+					
					<b>†</b>					
					<u> </u>					
7 Contractor's or Landowner's Cartific	ration: This water	ir well was	1 60	netructor	<u> </u>	reconstructed	or 3.	plugged	under my jurisdict	ion and
12/0/2010										
was completed on (mo/day/year)										
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/10/2010										
under the business name of Harp Well and Pump Service by (signature)  Todd S. Horb										

WATER WELL RECORD Form WWC-5 KSA 82a-1212