WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER FRACTION NW NWSedgwick SE 1 Т 27 S 2E E/W 1/4 Distance and direction from nearest town or city street address of well if located within city? 2503 N. Ridge Hurst Wichita, Kansas SHARP CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource 430 Walnut RR#,ST. ADDRESS,BOX #: CITY, STATE: Augusta, Kansas ZIP CODE: Application Number: 116 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. 60 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/18/11 Pump test data: Well water was hours of pumping @ ft. after qpm NW NE ft. after Est. Yield: gpm Well water was hours of pumping @ gpm Ī Bore Hole Diameter 12 to 116 WELL WATER TO BE USED AS 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE **9₩** 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial Was a chemical/bacteriological sample submitted to Department? ; If yes, what mo/day/yr was sample (NO Was Water Well Disinfected? (YES submitted 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Clamped SDR-26 Asbestos-Cement 8. Concrete tile 4 ABS 2. PVC 60 Dia. Blank casing diameter in. ft.. in. ft.. Dia. in. to ft. 12 2.35 Casing height above land surface: in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1. Steel 6. Concrete Tile 8. RMP (SR) 10 Asbestos-Cement 12. None used (open hole) 2 Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 3. Mill slot 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 5. Gauzed wrapped 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 60 to 114 ft.. From ft. ft. to From ft. to ft., From ft. to ft 24 ft. 114 **GRAVEL PACK INTERVALS:** From to ft., From to ft. ft. From to ft., From ft to ft. **GROUT MATERIALS:** Other 6 bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite 4 ft. 24 Grout Intervals: From ft., From ft. ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τо 0 3 topsoil 3 14 clav 14 116 gray shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed under my jurisdiction and 2/18/2011 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/28/2011

by (signature)

under the business name of Harp Well and Pump Service

Todd S. Harb