WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE NWNW 1/4 8 27 S 2E E/W Distance and direction from nearest town or city street address of well if located within city? 8504 E. Bridlewood Wichita, Kansas SHANNON, Dwayne WATER WELL OWNER: Board of Agriculture, Division of Water Resource 8504 E. Bridlewood RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE Application Number 85 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft **ELEVATION:** WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 14 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm ΝE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm ≌ Bore Hole Diameter 12 to 85 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only S₩ SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? (YES) Was Water Well Disinfected? NO 5 TYPE OF CASING USED: CASING JOINTS: (Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1 Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Dia. Dia Blank casing diameter 30 ft.. ft. in. ft., in. to in. to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1 Steel 12. None used (open hole) 2. Brass 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 85 30 ft. ft., From to From ft. From ft to ft., From ft ft. GRAVEL PACK INTERVALS: ft. to 85 ft., From ft. From ft. From ft. to ft., From to ft **GROUT MATERIALS:** Other bentonite hole plug 2. Cement Grout 3. Bentonite 1. Neat cement Grout Intervals: 4 From ft. 24 ft., From ft. to From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG То LITHOLOGIC LOG From Τо From 0 topsoil 3 10 clay 10 80 gray shale 80 85 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed plugged under my jurisdiction and

was completed on (mo/day/year) 3/18/2011 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/21/2011

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp