Form WWC-5 KSA 82a-1212 WATER WELL RECORD LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NW 1/4 NW1/4 NE 1/4 11 Т 27 S R **2E** E/W Distance and direction from nearest town or city street address of well if located within city? 2018 N. Clear Creek Wichita, Kansas RITCHIE BUILDING WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N. Bldg. 1000 Wichita, Kansas CITY, STATE: ZIP CODE Application Number 90 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: N WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NE-NW Est. Yield: apm Well water was ft. after hours of pumping @ gpm Ξ Bore Hole Diameter 12 to 90 ft W WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES submitted Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: CGlued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 5 30 ft. Dia. ft.. Dia ft. Blank casing diameter to to in to 12 Weight: 2.35 lbs. / ft Wall thickness or gauge No. .214 Casing height above land surface: TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1. Steel 8. RMP (\$R) 12. None used (open hole) 2. Brass 6. Concrete Tile Asbestos-Cement 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 7. Torch cut 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched 30 SCREEN - PERFORATION INTERVAL to ft., From ft. From ft. to From to ft., From ft. ft. to **GRAVEL PACK INTERVALS:** 24 ft. to From ft.. From ft. to ft. ft to ft.. From From ft. to ft. Other **GROUT MATERIALS:** 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft . From ft. to ft., From ft What is the nearest source of possible contamination: 10. Livestock pens 13. Insecticide storage 15 Oil well/Gas well 7. Pit privy 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 3 Watertight sewer line 6. Seepage pit How many feet? 10 ft. plus South Direction from well? LITHOLOGIC LOG From Τо LITHOLOGIC LOG From То 0 topsoil 3 10 clay 10 <u>75</u> shale 75 <u>78</u> limestone 78 90 gray shale

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/10/2011 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/12/2011 under the business name of Harp Well and Pump Service by (signature) Todd S. Horp