		WATER WELL RECORD	Form WW	/C-5 K	SA 82a-1212		
1 LOCATIO	N OF WATE	RWELL: FRACTION	SECT	ION NUMBER	R TOWNSHIP NUMBER	RANGE NUMBER	
Sedgv	vick	NW 1/4 SW 1/4 SI	E 1/4	8	T 27 S	R 2E E/W	
		nearest town or city street address of well if located within city?					
	N. Linde		nsas				
2 WATER WELL OWNER: DOWNING, Barry Board of Agriculture, Division of Water Resource							
RR#,ST.	ADDRESS				board of A	Agriculture, Division of Water Resource	
- parameter anti-constant	CITY,	STATE: Wichita, Kansas	None and the second	CODE:	Application I	lumber:	
3 LOCATE	E WELL'S LO N "X" IN SEC	CATION 4 DEPTH OF COMPLETED WELL:	90 ft.		ELEVATION:		
, WIITA	N N	Depth of groundwater Encountered:	ft.		ft.	ft.	
	-	WELL'S STATIC WATER LEVEL 20	FT. BELO	W LAND SU	JRFACE MEASURED ON m	o/day/yr: 11/16/11	
	· NW	-NE Pump test data: Well	water was		ft. after ho	urs of pumping @ gpm	
<u>o</u>		Est. Yield: gpm Well	water was		ft. after ho	urs of pumping @ gpm	
₩ <u> </u>		Bore Hole Diameter 12 in.	to 9	$oldsymbol{0}$ ft.	and in.	to ft.	
-	1	WELL WATER TO BE USED AS:			9. Dewat	ering 11. Injection well	
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below							
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? VES NO ; If yes, what mo/day/yr was sample							
	S	Was a chemical/bacteriological sample submitted submitted	to Department?	YES	NO ; If ye Vater Well Disinfected?	YES NO	
5 TYF	PE OF CAS	NG USED:		······································			
	. Steel	3. RPM (SR) 5. Wrought Iron 7. Fibergla	400	her (Specify	below) CASING JOINTS		
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Weided Clamped							
	ing diamete		in.	to	ft., Dia.	in, to ft.	
	_	10					
	_	,	2.35	s. / ft.	Wall thickness or g	auge No214	
1. Stee	TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)						
2. Bras	· · · · · · · · · · · · · · · · · · ·						
		·	10. A	3063103-061	12. None asca (op	on noicy	
1		RATION OPENINGS ARE:				44.14	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)							
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)							
SCREEN -	PERFORA	TION INTERVAL From 30 ft.	to 90	ft.,	From ft.	to ft.	
		From ft.	to	ft.,	From ft.	to ft.	
G	RAVEL PA	CK INTERVALS: From 24 ft.	to 90	ft.,	From ft.	to ft.	
			to		_	7.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							
Grout Intervals: From 4 ft. to 24 ft., From				to	ft., From	ft. to ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy				k pens	13. Insecticide storag	e 15. Oil well/Gas well	
The second secon				. Fuel storage 14. Ab		16. Other (specify below)	
2. dewer lines							
Direction 1	tight sewe	riline 6. Seepage pit 9. Feed yard North	12. Fertilize	Storage	How many fact? 1	0 ft plus	
From				То	How many feet? 10 ft. plus LITHOLOGIC LOG		
0	3	topsoil	110111	10	LITTIO	LOGIO LOG	
3	12	clay					
12	20	brown shale	***************************************				
20	90	gray shale					
	 			ļ	<u> </u>		
				 			
	<u> </u>		 				
				l			
7 Cont	tractoric or i	andowner's Certification: This water well was 1. constru-	ctod o ==	constructs	d or 3, plugged	under my jurisdiction and	
		11/1/2011		constructe		under my junsuiolion and	
was cor	mpleted on	(mo/day/year) 11/16/2011 and this rec	ord is true to the	best of my	knowledge and belief.		
,		Contractor's License No. 236 This water			d on (mo/day/year) 11	/18/2011	

by (signature)