WATER WELL RECORD Form WWC-5 KSA 82a-1212 TOWNSHIP NUMBER RANGE NUMBER SECTION NUMBER LOCATION OF WATER WELL: FRACTION Sedgwick NW \mathbf{SE} NE 11 27 S 2EE/W 1/4 Т R 1/4 Distance and direction from nearest town or city street address of well if located within city? 1934 N. Castlerock Court Wichita, Kansas WATER WELL OWNER: MCCLELLAN, Mike Enterprises Inc. Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1108 W. 34th N. CITY, STATE: Wichita, Kansas Application Number: ZIP CODE: 97 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm ΝW Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ⋝ 12 to 97 Bore Hole Diameter ft. WELL WATER TO BE USED AS 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning 2. Irrigation ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? YES Was Water Well Disinfected? submitted TYPE OF CASING USED: CASING JOINTS: Clued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 30 ft., Dia. ft. Blank casing diameter Dia. in in. to in ft.. 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3. Stainless Steel 5. Fiberglass 1. Steel 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 2. Louvered shutter 8. Saw cut 10. Other (specify) 4. Key punched 6. Wire wrapped SCREEN - PERFORATION INTERVAL 30 ft ft., From From to ft to ft. ft. to ft., From From ft. to ft. GRAVEL PACK INTERVALS: 24 ft. to ft . From ft to From ft. ft From to ft., From ft. to ft. Other **GROUT MATERIALS:** bentonite hole plug 6 2. Cement Grout 3 Bentonite 1. Neat cement Grout Intervals: 4 ft. 24 ft., From ft. ft. to ft., From What is the nearest source of possible contamination: 15. Oil well/Gas well 10. Livestock pens 13. Insecticide storage 7. Pit privy 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14 Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line How many feet? 10 ft. plus Direction from well? South LITHOLOGIC LOG From Τо LITHOLOGIC LOG From Τо 0 topsoil clay 3 10 10 30 brown shale 30 90 gray shale 90 97 limestone and gray shale

under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed 3. plugged or and this record is true to the best of my knowledge and belief.

was completed on (mo/day/year) 4/9/2012

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

4/10/2012

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp