		WATER W	ELL RECORD) Fo	rm WV	VC-5 K	SA 82a-1	1212			
1 LOCATION OF WATER WELL: FRACTION								SHIP NUMBER	RAN	RANGE NUMBER	
Sedgwick		SE 1/4		SE	1/4	9	Т	27 S	R	2E	Ε/W
Distance and direction fro	•		•								
10621 Crestw			ita, Kansas								
2 WATER WELL O		CHIE BUILD	EKS					Board of A	griculture, Divisio	n of Wat	er Resource
RR#,ST. ADDRESS		E. 22nd N. nita, Kansas							_		
				78		P CODE:	ELEVATIO	Application N	umber:		
UCCATE WELL'S LO	CTION BOX:	DEPTH OF COMP		70	ft.		ELEVATIO				
N N		pth of groundwater		Λ.	ft.			ft.			ft.
		ELL'S STATIC WA				W LAND SU		ASURED ON mo		4/25/1	12
NW	- NE			ell water			ft. after		irs of pumping		gpm
w Miles	F B	Est. Yield: ore Hole Diameter	1.0	ell wate	rwas to 7	78 ft.	ft. after and		ırs of pumping	_	gpm
["		ELL WATER TO B			10 /	O II.	anu	in.		to Injecti	ft. on well
sw -	_ I I			lic wate	r supply	7. Lawn a	nd garden o	9. Dewate	9	•	cify below)
	2	!. Irrigation 4.	Industrial 6. Oil 1	field wat	ter supply	8. Air cor	nditioning	10. Monito		. (. po	o, 20.0,
s			riological sample submit	tted to De	partment?	YES	NO	•	, what mo/day	•	•
5 TYPE OF CAS		bmitted					Vater Well Di		(YES)	NC	
5 TYPE OF CAS	SING USED: 3. RPM (SR	5. Wrought	Iron 7. Fibe	rglass	9. Ot	ther (Specify	below) (CASING JOINTS			hreaded
2. PVC	> 4. ABS	6. Asbestos	s-Cement 8. Con	crete tile	SDI	R-26			Welded	(Clamped
Blank casing diameter		in. to	40 ft., Di	ia.	in.	to	ft.,	Dia.	in. to	,	ft.
Casing height above	_	12 in.,	Weigh			os. / ft.					14.
TYPE OF SCREEN			vveigi	n. 2	J.J	os. / It.	vva	II thickness or ga	uge No	214	
Į.	3. Stainless Steel	5. Fiberglass	7. PVC	>	9. A	BS	11.	Other (specify)			
	1. Galvanized	6. Concrete T	ile 8. RMP	(SR)	10. A	sbestos-Cer	ment 12.	None used (ope	n hole)		
SCREEN OR PERFO	DRATION OPENING	3S ARF									
1. Continuous slot			Gauzed wrapped		7. To	rch cut	9. [Orilled holes	11. No	ne (ope	en hole)
2. Louvered shutte	er 4. Key pu		Wire wrapped			w cut		Other (specify)			,
		inched o. t				w cut	10. \	other (specify)			
SCREEN - PERFORA	ATION INTERVAL	From	40 ft.	to	78	ft.,	From	ft,	to)	ft.
		From	ft.	to		ft.,	From	ft.	to)	ft.
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	78	ft.,	From	ft.	to		ft.
		From	ft.	to		ft.,	From	ft.	to)	ft.
6 GROUT MATER	IALS: 1. Neat o	cement	2. Cement Grou	t	3	Bentonite		Other ber	itonite hol	e plug	
Grout Intervals:	From 4	ft. to	24 ft., F	rom	ft.	to	ft.,		ft.	to	ft.
What is the nearest so	•	-	. Pit privy	10.	Livestoc	k pens	13 lns	ecticide storage	15 Oil v	vell/Ga	s well
1. Septic tank 4. Lateral lines						rage		nsecticide storage 15. Oil well/Gas well Abandon water well 16. Other (specify below)			
2. Sewer lines	5. Cess P					_	14. AD	andon water we	H	(, 20 .0,
3. Watertight sewer Direction from well?	er line 6. Seepag West	ge pit 9	. Feed yard	12	. Fertilizei	storage	Цои	many feet? 10	oft plue		
From To		LITHOLOGIC	CLOG		From	То	HOW		OGIC LO		
0 3	topsoil	LITTIOLOGIC	7 200		1 10111	10		LITTIOL	OGIO LO		
3 15	clav										
15 40	brown shale										
40 75	gray shale										
75 78	limestone										
				-							

						ļ					
	 										
	 			-+					······································		·
7 Contractor's or I	andowner's Cortific	cation: This water	well was 1. const	ructod) 2 ===	constructo	l or 3	nlunned	under mu i	iediot:-	and
		4/25/2012				constructed		plugged	under my jur	เอนเนเปไ	i and
was completed on	,					•	knowledge a				
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/30/2012											
under the business	name of Harp	Well and Pun	np Service		by (sig	gnature)	-	Todds	S Ha	vħ	
									J. 1000	<u> </u>	