	WATER WELL RECORD	D Form WW	/C-5 KSA	82a-1212	
1 LOCATION OF WATER WELL:	FRACTION		ION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick	NE 1/4 NW 1/4	SE 1/4	1	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?					
15502 E. Mainsgate Wichita, Kansas 2 WATER WELL OWNER: RITCHIE BUILDERS					
	00 E. 22nd Bldg.1000			Board of Agrid	culture, Division of Water Resource
	ichita, Kansas	70	P CODE:	Application Num	her:
	4 DEPTH OF COMPLETED WELL:	120 ft.		VATION:	
WITH AN "X" IN SECTION BOX:		ft.		ft.	ft.
	Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL	(a)			
		Vell water was		CE MEASURED ON mo/d ft. after hours	
0 N₩NE-		Vell water was			of pumping @ gpm of pumping @ gpm
E W	Bore Hole Diameter 12 in.	to 1		and in.	to ft.
Z " X L	WELL WATER TO BE USED AS:			9 Dewaterir	44 1
SW SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)					
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample					
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, What mo/day/yr was sample submitted Was Water Well Disinfected? (YES) NO					
1. Steel 3. RPM (SR)					
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Weided Clamped					
Blank casing diameter 5	in. to 60 ft., D	Dia. in.	to	ft., Dia. i	n. to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill	I slot 5. Gauzed wrapped	7. Tor	ch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key	y punched 6. Wire wrapped	8. Sav	v cut	10. Other (specify)	
SCREEN - PERFORATION INTERVA	L From 60 ft.	to 120	ft., F	rom ft.	to ft.
	From ft.	to	ft., F	rom ft.	to ft.
GRAVEL PACK INTERVALS	Erom 24 ft.	to 120	ft., Fi	rom ft.	to ft.
	From ft.	to	ft., F	rom ft.	to ft.
6 GROUT MATERIALS: 1. Ne	at cement 2. Cement Grou	ut 3	Bentonite	Other bent	onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible	7 Dit privat	10. Livestock			
1. Septic tank 4. Lateral lines (1. Constitution of the instantial constited constitution of the instantial constitution of					
2. Sewer lines 0. Cess Pool					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? North From To	LITHOLOGIC LOG	From	То	How many feet? 10 f	
0 3 topsoil	EITHOLOGIC ECC				GICLOG
3 15 clay					
15 65 brown shal	e				
65 120 gray shale					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and					
was completed on (mo/day/year) 5/14/2012 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/16/2012					
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb					