Form WWC-5 KSA 82a-1212 WATER WELL RECORD 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER FRACTION  $\mathbf{SW}$ NW SE 3 27 Sedgwick Т S 2E 1/4 1/4 Ε/W Distance and direction from nearest town or city street address of well if located within city? 12017 E. Boxthorn Wichita, Kansas SARDJINI, VDESILVA RANASI WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 12017 E. Boxthorn Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 100 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft. 50 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/13/12 Pump test data: Well water was ft. after hours of pumping @ gpm NW Well water was ft. after hours of pumping @ gpm Est. Yield: apm 12 to 100 Ξ ft. Bore Hole Diameter in and WELL WATER TO BE USED AS: 11. injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW -SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 8. Air conditioning 2. Irrigation 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS 5 50 Dia. Dia. Blank casing diameter in. ft. to 12 2.35 Wall thickness or gauge No. Casing height above land surface: in.. Weight: ibs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberolass 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2 Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1 Continuous slot 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) 50 100 SCREEN - PERFORATION INTERVAL ft. ft., From From to ft. ft. to ft. From to ft., From ft. to 24 ft. to 100 GRAVEL PACK INTERVALS: From ft., From ft. ft. From to ft.. From ft. to ft. **GROUT MATERIALS** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 24 ft., From ft. ft., From ft. to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. West 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From To O topsoil 3 45 clay 45 96 gray shale <u>96</u> 100 limestone under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. 8/13/2012 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief 8/16/2012 This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service