WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION RANGE NUMBER NW 1/4 ΝE Sedgwick SE SE 1/4 Т 27 S E/W Distance and direction from nearest town or city street address of well if located within city? 15710 E. Camden Chase Wichita, Kansas **NIES CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303 Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 124 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. Ν WELL'S STATIC WATER LEVEL 42 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/12/13 Pumo test data: Well water was ft. after hours of pumping @ NW NE gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gom ⋝ Bore Hole Diameter 12 124 ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW X 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 **50** Blank casing diameter to Dia. Dia. in. to ft., ft. in. to 12 Casing height above land surface: 2.35 in.. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 2 Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 4 Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 9. Drilled holes 5. Gauzed wrapped 7. Torch cut 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 50 124 From to ft.. From ft. ft. to ft., From ft to ft. GRAVEL PACK INTERVALS: 24 ft to 124 From ft., From ft to ft. From ft. to ft.. From ft. **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 24 ft. From ft. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit How many feet? 10 ft. plus Direction from well? From LITHOLOGIC LOG Τо From To LITHOLOGIC LOG topsoil 3 10 clay 10 40 brown shale gray shale 40 <u> 124</u> Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 9/12/2013 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/16/2013 Todd S. Harb under the business name of Harp Well and Pump Service by (signature)