			WATER	WELL R	ECORD	Form W	WC-5	KSA 82a-12	12		
1 LOCATION OF W	VATER WI	ELL:	FRACTION	SE SW		l -	CTION NUMBE		IP NUMBER	RANGE N	
Sedgwick			10 ME 10	<u> </u>	1/4 84	1/4	3	T 2	27 s	R 2	E E/W
Distance and direction from nearest town or city street address of well if located within city? 2424 Woodridge Ct. Wichita, Kansas											
			V Davillo		ta, Kansas						
2 WATER WE			Y, Paul Ho Box 12107	mes, LL	C				Board of Agric	culture, Division of	Water Resource
RR#,ST. ADDR	ITY, STA		ita, Kansas				ZID CODE:		Application Num	her.	
					NELL	4 0 0	ZIP CODE:	ELEVATION:	Application (4din	iber.	
3 LOCATE WELL WITH AN "X" IN		ıβοx: ├─	DEPTH OF CO					ELEVATION.			
1,	N		oth of groundwa				ft.		ft.	10.0	ft.
		WE	LL'S STATIC V				OW LAND S		URED ON mo/d	.,,	23/13
		<u></u>		Pump test d		water was		ft. after		of pumping @	gpn
w Mile			Est. Yield:	gpm	_	water was	100	ft. after		of pumping @	gpm
≥ w			ore Hole Diame		.2 in.	to	100 f	t. and	in.	to	ft.
sw		_ 1	ELL WATER TO Domestic	BE USED 3. Feedlot		water euenly	C7 Lawn	and garden on	9. Dewaterii		ection well
		N I I	Irrigation	4. Industri		d water supp		nditioning	10. Monitorin		pecify below
	S		as a chemical/ba		-	• • •	•	NO		vhat mo/day/yr	was sample
	3		omitted			то воранилони.		Water Well Disir	nfected?	YES	NO
5 TYPE OF	CASING	USED:	E \M/sous	ahi lann	7. Fibergla	9.0	Other (Specif	fv below) CA	SING JOINTS: (Glued	Threaded
1. Steel	l	3. RPM (SR	5. Wroug	jni iron	7. Fibergia		OR-26	,, 20.0,		Welded	Clamped
2. PVC	\supset	4. ABS	6. Asbes	tos-Cemen	t 8. Concret	e tile SL)K-20				,
Blank casing dia	meter	5 i	in. to	40 f	t., Dia.	in.	to	ft.,	Dia. i	in. to	ft.
Casing height al	bove land	d surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall t	hickness or gaug	je No214	1
TYPE OF SCRE			•								
1. Steel		inless Steel	5. Fibergla	ss (7. PVC	9.	ABS	11. C	ther (specify)		
2. Brass	4. Ga	Ivanized	6. Concrete	e Tile	8. RMP (SF	₹) 10.	Asbestos-Ce	ement 12. N	one used (open	hole)	
SCREEN OR PE	DEODAT	ION OBENING	C ADE								
1. Continuous		3. Mill sig		Gauzed v	uranned	7 T	orch cut	9 Dri	lled holes	11. None (onen hole)
											орон ного,
2. Louvered sh	nutter	4. Key pu	inched t	6. Wire wra	ppea	8.3	aw cut	10. Oti	ner (specify)		
SCREEN - PERF	ORATIO	N INTERVAL	From	40	ft.	to 100	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
GRAVEL	PACK I	NTERVALS:	From	24	ft.	to 100	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MAT	TERIALS										
رع		1. 11041.0			ment Grout		3. Bentonit		Dent	onite hole pl	_
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. What is the nearest source of possible contamination:								ft. to	ft.		
1. Septic tank	7 Die gring 10						ck pens	13. Insec	ticide storage	15. Oil well/	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (speci									pecify below)		
3 Watertight s		6. Seepag	ne pit	9. Feed ya	ard	12. Fertiliz	er storage				
Direction from we		West	,	•			_	How m	nany feet? 10 f	t. plus	
From To		L	ITHOLOG	IC LOG		From	То	I	LITHOLO		
0 3	tor	soil									
3 40											
40 10	0 gr	y shale									
ļ											
								.			
 											
						-	+				
							†				
		<u></u>									
7 Contractor's	s or Land	owner's Certific	ation: This wat	er well was	1. construc	ted 2 r	econstructe	ed or 3.	plugged (under my jurisdic	tion and
was completed on (mo/day/year) 10-23-2013 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10-25-2013											
under the busir	ness nam	e of Harp V	Well and P	ump Ser	vice	by (signature)	T	odd S	. Hart)
1										E	