


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 NE 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W			
Distance and direction from nearest town or city street address of well if located within city? 800 N. Fair Oaks Andover, Kansas							
2 WATER WELL OWNER: RR#, ST. ADDRESS, BOX #: GEAR HART HOMES 1111 N. Coachouse Ct.	Board of Agriculture, Division of Water Resource CITY, STATE: Wichita, Kansas						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 82 ft.	ELEVATION: 25 FT. BELOW LAND SURFACE MEASURED ON 10/21/13					
Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL		ft.	ft.	ft.			
Pump test data: Est. Yield: gpm	Well water was	ft. after	hours of pumping @	gpm			
Bore Hole Diameter 12 in.	Well water was	ft. after	hours of pumping @	gpm			
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only	8. Air conditioning	9. Dewatering	11. Injection well				
2. Irrigation 4. Industrial 6. Oil field water supply	10. Monitoring well	12. Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? submitted	YES NO	; If yes, what mo/day/yr was sample					
	Was Water Well Disinfected? YES	NO					
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued			
4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Threaded Welded Clamped			
Blank casing diameter 5 in.	to 32 ft.	Dia.	in. to	ft. Dia. in. to ft.			
Casing height above land surface: 12 in.,		Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 2. Brass 4. Galvanized 6. Concrete Tile	7. PVC	9. ABS	11. Other (specify)				
8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)				
	8. Saw cut	10. Other (specify)					
SCREEN - PERFORATION INTERVAL	From 32 ft.	to 82 ft.,	From	ft.	to ft.		
	From	ft.,	From	ft.	to ft.		
GRAVEL PACK INTERVALS:	From 24 ft.	to 82 ft.,	From	ft.	to ft.		
	From	ft.,	From	ft.	to ft.		
6 GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug			
Grout Intervals: From 4 ft.	to 24 ft.,	From	ft. to	ft.,	From ft. to ft.		
What is the nearest source of possible contamination:							
1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 3. Watertight sewer line	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well			
6. Seepage pit	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)			
Direction from well? North	How many feet? 15 ft. plus						
From	To	LITHOLOGIC LOG		From	To	LITHOLOGIC LOG	
0	3	topsoil					
3	8	clay					
8	25	brown shale					
25	82	gray shale					
Drill Log							
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and							
was completed on (mo/day/year) 10-21-2013 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 10-23-2013						
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp						