WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE SE NE 3 27 2EТ S R E/W 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 2734 N. Woodridge Wichita, Kansas ROBL CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 5842 W. 21st N. CITY, STATE: Wichita, Kansas ZIP CODE: Application Number: 116 **ELEVATION:** LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 57 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 1/6/14 Pump test data: Well water was hours of pumping @ · NE ft. after gpm -NW Est. Yield: gpm Well water was ft, after hours of pumping @ gpm Ξ 12 to 116 Bore Hole Diameter ft. and in ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 3. Feedlot 5. Public water supply 7. Lawn and garden only 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? YES submitted Was Water Well Disinfected? YES NO TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 50 Blank casing diameter in. ft.. Dia. iń. to ft., Dia. in. to ft. Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 3 Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped 55 SCREEN - PERFORATION INTERVAL ft. 116 ft., From to From ft. From ft. to ft., From ft. to ft. **GRAVEL PACK INTERVALS:** 24 ft. to 116 From ft., From ft. to ft, From ft. to ft., From ft. **GROUT MATERIALS:** Other 6 2. Cement Grout 3. Bentonite bentonite hole plug 1. Neat cement Grout Intervals: 4 ft. 24 ft., From ft. to ft.. From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? From From LITHOLOGIC LOG To LITHOLOGIC LOG To 0 3 topsoil 3 15 clay 15 51 brown shale 51 grey shale 116 Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and

1/6/14 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 1/7/14 Todd S. Harp under the business name of Harp Well and Pump Service by (signature) - 1.7kg