WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: RANGE NUMBER SECTION NUMBER TOWNSHIP NUMBER FRACTION NW NE 8 27 2E Sedgwick 1/4 1/4 Т S Ε/W Distance and direction from nearest town or city street address of well if located within city? 10411 E. Summerfield Wichita, Kansas **NIES CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource 10333 E. 21st #303 RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 76 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Well water was Pump test data: ft. after hours of pumping @ gpm ΝE MW Well water was ft. after hours of pumping @ gpm Est. Yield: gpm 12 76 Ξ Bore Hole Diameter and in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply Lawn and garden only SW SE 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) NO submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 ft., Blank casing diameter in. to 35 ft.. Dia. in to Dia. in. to fi 12 Weight: 2.35 Wall thickness or gauge No. Casing height above land surface: lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. **P**VC 9 ABS 11. Other (specify) 3 Stainless Steel 5 Fiberolass 1. Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9 Drilled holes 11. None (open hole) 1. Continuous slot 6. Wire wrapped 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 76 SCREEN - PERFORATION INTERVAL 35 ft. to ft... From From ft ft. to From ft. to ft.. From ft. to ft. 24 **GRAVEL PACK INTERVALS:** to 76 From ft... From ft tο ft. ft. From to ft., From to ft. **GROUT MATERIALS:** Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: ft 24 From ft., ft. ft. From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oit well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit East How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Tο From Тο topsoil 28 clav 28 <u>70</u> gray shale 70 limestone

Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and was completed on (mo/day/year) 3/6/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/7/14 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp