WATER WELL RECORD	Form WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	I	RANGE NUMBER
Sedgwick SE NE 1/4 SE 1/4 SE	1/4 1	т 27 <b>2%</b> s	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?			
15907 E. Boxthorn Wichita, Kansas			
WATER WELL OWNER: RITCHIE BUILDER		Board of Ag	riculture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N., Bldg. 1000	717.007	_	
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	mber:
WITH AN "X" IN SECTION BOX:	.15 ft.	ELEVATION:	
Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 50		JRFACE MEASURED ON mo/	• •
'''   ''-	ater was		s of pumping @ gpm
	ater was		s of pumping @ gpm
Bore Hole Diameter 12 in.  WELL WATER TO BE USED AS:	to 115 ft.		to ft.
I THELE WATER TO BE COLD AC.	ater supply 7. Lawn a	9. Dewater	ing 11. Injection well 12. Other (Specify below)
	water supply 8. Air cor		
S Was a chemical/bacteriological sample submitted to			what mo/day/yr was sample
submitted	Was V	Vater Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglas	9. Other (Specify	below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR) 6. Asbestos-Cement 8. Concrete	tile SDR-26		Welded Clamped
4. ADS	ine		
Blank casing diameter 5 in. to 50 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	0.400	11 Other (enecify)	
	9. ABS	11. Other (specify)	. h
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer	nent 12. None used (open	noie)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 50 ft.	to 115 ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft.	to 115 ft.,	From ft.	to ft.
	to ft.,	From ft.	to ft.
C CROUT MATERIALS.	,		
1. Neat cement 2. Cement Grout	3. Bentonite		tonite hole plug
What is the nearest source of possible contamination:	ft, to	ft., From	ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilizer storage		
Direction from well? West		How many feet? 10	ft. plus
From To LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG
0 3 topsoil			
3 15 clay			
15 110 gray shale			
110 115 limestone			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	<del>                                     </del>		
	+ +		
7 Comments of advantage of the Till Comments of the		l or 0 mluses	under my jurisdiction and
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and			
was completed on (mo/day/year) 12/15/2013 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/18/2012			
under the business name of Harp Well and Pump Service	by (signature)	Todd S	. Harb
·			- ,,