		WELL REC		orm WW		SA 82a-12				
1 LOCATION OF WATER WELL:	FRACTION	SW SE NW 1/4 800 1/		1	ION NUMBER	_	P NUMBER	RANGE NI R 2E		
Sedgwick		17 7 7 7		1/4	112	T 2	7 s	R 21	, E/VV	
Distance and direction from nearest town or city street address of well if located within city? 1539 N. Ridgehurst Wichita, Kansas										
1539 N. Ridgehurst	SHARP HOMI		411545							
2 WATER WELL OWNER: SHARP HOMES RR#,ST. ADDRESS,BOX #: 430 Walnut Board of Agriculture, Division of Water Resource										
CITY, STATE:	Wichita, Kansa	as		711	CODE: 6	7230	Application Num	ber:		
3 LOCATE WELL'S LOCATION		OMPLETED WELI	110		OODL.	ELEVATION:			*****	
WITH AN "X" IN SECTION BOX:	 		_ ,	ft.			ft.		ft.	
N N	, ' ~	vater Encountered			AVI AND CI	IDEACE MEAC		av/vr: 4/15		
	WELLSSTATIC	WATER LEVEL			W LAND SC	ft. after	JRED ON mo/d	of pumping @	gpm	
NWNE	Est. Yield:	Pump test data: gpm	Well wate Well wate			ft. after		of pumping @	gpm	
w Wile	E Bore Hole Diam	1.0	in.	to 1	10 ft.		in.	to	ft.	
_		O BE USED AS:	41.				9. Dewaterin		ction well	
- SW - SE	1. Domestic	3. Feedlot	5. Public wate	er supply	7. Lawn a	ınd garden onl		_	pecify below)	
	2. Irrigation	4. Industrial	6. Oil field wa	ter supply	8. Air con	ditioning	10. Monitorin	-		
S	Was a chemical/b submitted	acteriological sample	e submitted to De	epartment?	YES	NO Vater Well Disin		/hat mo/day/yr v	vas sampie NO	
E TYPE OF CASING HOES										
5 TYPE OF CASING USED	D: S. Wro RPM (SR)	ught Iron	7. Fiberglass	9. Ot	her (Specify	below) CAS	SING JOINTS: (Glued	Threaded	
	• •	estos-Cement {	8. Concrete tile	SDI	R-26			Welded	Clamped	
Blank casing diameter	5 in. to	50 ft.,	Dia.	in.	to	ft.,	Dia.	n. to	ft.	
	10				_					
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless		lass $\sqrt{7}$	PVC	9. Al	BS	11. Ot	her (specify)			
2. Brass 4. Galvaniz	9		. RMP (SR)		sbestos-Cer	ment 12. No	one used (open l	hole)		
			(,					·		
SCREEN OR PERFORATION Of 1. Continuous slot	3. Mill slot	5 Gauzed wran	ned	7 To	rch cut	9 Dril	led holes	11. None (c	pen hole)	
1										
2. Louvered shutter	4. Key punched	6. Wire wrapped	1	8. Sa	w cut	10. Oth	er (specify)			
SCREEN - PERFORATION INT	ERVAL From	50 ft.	to	110	ft.,	From	ft.	to	ft.	
	From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTER	VALS: From	24 ft.	to	110	ft.,	From	ft.	to	ft.	
	From	ft,	to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS:	1. Neat cement	2. Cemen	t Grout		B. Bentonite		Other bent	onite hole pl	ug	
								ft.		
What is the nearest source of po	ossible contamination:	,						45 00	S11	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas we										
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)										
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well? East					T	How m	any feet? 10			
From To	LITHOLO	GIC LOG		From	То		LITHOLO	GIC LOG		
0 3 topsoil										
3 20 clay 20 110 gray sh	a a la									
20 110 gray sh	laie									
					 					
										
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and										
was completed on (mo/day/year) 4/15/2014 and this record is true to the best of my knowledge and belief.										
4.17.2014										
Turisda Valor Vari de la Carriera de										
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										