		WATE					Form			SA 82a-	1212					
1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW NE SE NW 800 1/4 800 1/4						1	TION NUMBER	1	TOWNSHIP NUMBER T 27 S			RANGE NUMBER R 2E E/W		
	om nearest town or city s						1/4	Ц	34	1	21	٥		R 21	C E/W	
1823 S. Lynn				ichita												
2 WATER WELL		DERS, T	•								D.	and of Apr	ioulturo Di	dains of M	Vater Resource	
RR#,ST. ADDRESS		S. Lynn										•		VISION OF V	vater Resource	
··· y		ita, Kans		TED 14			50		P CODE:	EL EVATIO	- ' '	cation Nur	nber:			
J LOCATE WELL'S L WITH AN "X" IN SE	CTION BOX:	EPTH OF (•	,0	ft. ft.		ELEVATIO		ft.			ft.	
N N		th of ground LL'S STATI				20	ET		W LAND SU	DEACE ME			day/yr	3/25		
- NW	NE			test da		Well wa			W LAND GO	ft. after			of pumpi		gpr	
w W	· ·	Est. Yield:	•	gpm		Well wa				ft. after	•		s of pump		gpm	
		re Hole Dia		12		٦.		to 6	50 ft.	and		in.		to	ft.	
SW		LL WATER Domestic		USED A		Public w	ater sı	ınnlv	<7. Lawn a	nd garden	9. l	Dewateri	-		ction well	
1		Irrigation		dustria		Oil field v						Monitoria		otner (Sp	pecify below	
S		as a chemical	/bacteriol	ogical sa					YES	NO	>	· ·	_		vas sample	
5 TYPE OF CA		mitted								/ater Well D			YES		NO	
1. Steel	3. RPM (SR)	5. Wr	ought Iro	on	7. F	Fiberglass	5		ther (Specify	below) (CASING J	OINTS: (Glued Welded)	Threaded	
2. PVC	4. ABS	6. Asl	bestos-C	ement	8. 0	Concrete	tile	SDI	R-26				weided		Clamped	
Blank casing diamet	ter 5 in	n. te	o 25	5 ft.,	,	Dia.		in.	to	ft.,	Dia.		in.	to	ft.	
Casing height abov	e land surface:	12	in.,		W	eight:	2.35	5 II	os. / ft.	Wa	II thicknes	s or gaug	ge No.	.214		
	OR PERFORATION I			_							 .					
	3. Stainless Steel	5. Fiber	-	(7, P\			9. A			. Other (sp		h - 1-1			
	4. Galvanized	6. Conc	rete i lie		8. K	MP (SR)		10. A	sbestos-Cen	ient 12	. None use	ea (open	noie)			
1. Continuous slo	ORATION OPENINGS ot 3. Mill slot		5 Ga	uzed w	ranner	4		7 To	rch cut	9 1	Orilled hol	los.	11	None (o	nen hole)	
2. Louvered shutter 4. Key punched			5. Gauzed wrapped 6. Wire wrapped					7. Torch cut 8. Saw cut			9. Drilled holes 10. Other (specify)			11. None (open hole)		
	, p		O. 44 11		•					10. (other (spe	ecity)				
SCREEN - PERFOR	ATION INTERVAL	From -		25	ft.	to		60	ft.,	From		ft.		to	ft.	
GBAVEL BA	ACK INTERVALS:	From		24	ft. ft.	to		۷0	ft.,	From		ft.		to	ft.	
GRAVELPA	ACK INTERVALS:	From		24				60	ft.,	From -		ft.		to	ft.	
6 GROUT MATER	DIAL C.	From			ft.		0		ft.,	From		ft.		to	ft.	
GROUT MATER Grout Intervals:	RIALS: 1. Neat ce From 4	ement ft.	to	2. Cem 24	-	-			. Bentonite		Other		onite h	iole pl	ug	
	source of possible con			24	ft.,	Fro m		ft.	to	ft.,	Fro	ım	ft.	to	ft.	
1. Septic tank 4. Lateral lines 7. Pit priv							10. Liv	estoc	k pens	13. Ins	ecticide s	torage		il well/G		
2. Sewer lines	5. Cess Po	ool		ewage	-	n	11. Fu	el sto	rage	14. Ab a	andon wa	ter well	16. Q	ther (sp	ecify below)	
	er line 6. Seepage South	e pit	9. F	eed yar	ď		12. Fe i	rtilizer	storage			10.4	P41			
Direction from well? From To		ITHOLO	GICT	OG			Fr	om	То	How	many fee		GIC L	<u> </u>		
0 3	topsoil	IIIIOEC	<u> </u>				 ' '	OIII	10		<u> </u>	HOLO	OIC L	<u> </u>		
3 20	clay															
20 60	gray shale															
							+									
							-	-		·						
	 						 									
							+									
	 			-		,	+-	-								
	1															

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 3/25/2014 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 3/27/2014

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp