

1 LOCATION OF WATER WELL:		Fraction <u>SE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ SW $\frac{1}{4}$		Section Number	Township Number	Range Number
County: <u>Sedgwick</u>				<u>13</u>	<u>T 27 S</u>	<u>R 2</u> EW
Distance and direction from nearest town or city street address of well if located within city?						
<u>756 N. Stagecoach Rd., Wichita, KS 67230</u>						<u>EAST</u>
2 WATER WELL OWNER: <u>Greg Busch</u>						
RR#, St. Address, Box # : <u>756 N. Stagecoach Rd.</u>				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Wichita, KS 67230</u>				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>88</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL: <u>22</u> ft. below land surface measured on mo/day/yr <u>7/23/98</u>				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter: <u>9</u> in. to <u>88</u> ft., and in. to ft.				
		WELL WATER TO BE USED AS:				
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ☒ Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes ☒ No				
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded						
Blank casing diameter: <u>5</u> in. to <u>48</u> ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface: <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR26</u>						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped ☒ Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>88</u> ft., From ft. to ft.						
6 GROUT MATERIAL:						
1 Neat cement 2 Cement grout ☒ Bentonite 4 Other Grout intervals: From <u>4</u> ft. to <u>88</u> ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage						
Direction from well? How many feet?						
FROM		TO		LITHOLOGIC LOG		PLUGGING INTERVALS
0		20		Clay		
20		40		Shale & Clay		
40		50		Lime		
50		80		Shale with lime streaks		
80		88		Cherty Lime		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7/23/98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>171</u> This Water Well Record was completed on (mo/day/yr) <u>7/29/98</u> under the business name of <u>G&S Drilling, Inc.</u> by (signature) <u>[Signature]</u>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answer. Send top of record to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4