WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.				
		Fraction			Section Number Township No. Range Number 26 T 27 S R 2 ZE W			
County: Sed		1/4 NW 1/4						
Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees) Longitude: (in decimal degrees)			
840 S. Glenwood Ct					Flevation:			
Wichita, KS 67230					Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Zimbelman Construction					Collection Method:			
RR#, Street Address, Box #: 8737 N. Northridae Ct					GPS unit (Make/Model:) Digital Map/Photo, Topographic Map, Land Survey			
City, State, ZIP Code : Wichita. KS 67205					Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
1 A DEPTH OF COMPLETED WELL, 199								
	The state of the s							
N Depth(s) Groundwater Electronic (1). See that the second of the second								
Pump test data: Well water was								
$[-NW^{-1}]^{-NE^{-1}}$ by $xx + xy + yy + yy + yy + yy + yy + yy$								
" The supply water to be used as the public water supply Geothermal Injection well								
Demostic Defectly below Dil field water supply Dewatering Uther (Specify below)								
SwSB								
Was a chemical/bacteriological sample submitted to Department? Yes No								
s If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? ₩ Yes □ No								
5 TYPE OF CASING USED: Steel PVC Other								
Threaded								
Casing height above land surface in., Weight 4.9 wall unexpess of gauge 140								
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
The second of th								
From ## to								
CDAVEL DACK INTERVALS: From 20 ft to 100 ft. From								
E θ to # From Π. 10 II.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage					ge Abandoned water well			
Sewer lines Separate and Separate Feedbaard Feedbaard Oil well/gas well								
Direction from well South Distance from well 30.								
FROM TO	LITHOLO	GIC LOG	FROM	TO	LITHO. I	LOG (cont.) of PL	UGGING INTERVALS	
0 3	Topsoil		ļ					
3 30	Clav							
30 100	Limestone		 					
 			 					
 								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was occurrenced, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) .99(19/29/14 and this record is true to the best of my knowledge and construction and was completed on (mo/day/year) .96(19/2014								
		DIEACE DDECC FIDMI	Yand PRINT	NESTIV PIE	ease nu in bian	KS THE CHOCK THE COLLS	Ct mis wors. Deme one copy	
under the business name of Territer of the street of t								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constant of the const								
http://www.kdheks.gov/waterwell/index.html								