		WATER WI	LL REC	ORD 1	orm W	NC-5	KSA 82a-12	212		
1 LOCATION OF WATE	ER WELL:	FRACTION	GTT!			CTION NUMBI	1	HIP NUMBER	RANGE N	
Sedgwick		NE 1/4		/4 SE	1/4	34	T	27 s	R 2	E E/W
Distance and direction fro	-			•						
2204 S. Mich			a, Kansas	S						
2 WATER WELL		LARD, Elliott	t					Poord of Aco	culture, Division of	Matar Benouse
RR#,ST. ADDRES		S. Michelle					(=0.0=	Board of Agr	culture, Division of	water Resource
CITY	STATE: Wich	ita, Kansas				IP CODE:	67207	Application Nun	nber:	
3 LOCATE WELL'S L	OCATION 4 D	EPTH OF COMPI	LETED WEL	_L: 9	4 ft.		ELEVATION			
WITH AN "X" IN SE	Dep	th of groundwater	Encountere	d:	f	t.		ft.		ft.
	WE	LL'S STATIC WA	TER LEVEL	45	FT. BELO	OW LAND S	SURFACE MEAS	SURED ON mo/o	lav/vr: 7/1	0/14
NW NW	NE		np test data:				ft. after		of pumping @	gpm
1 1 1	INE	Est. Yield:	gpm		iter was		ft. after		of pumping @	gpm
w M	E Bo	re Hole Diameter	12	in.	to	94	ft. and	in.	to	ft.
-	1 1	LL WATER TO BI			.0		ii. Giid		44 1	ection well
sw	1		Feedlot		ater supply	7. Lawn	and garden or	9. Dewateri		specify below
		Irrigation 4.1	Industrial	6. Oil field v			onditioning	10. Monitorii		pecity below,
	Wa	as a chemical/bacteri				YES	(NO)	; If yes,	what mo/day/yr	was sample
	sub	mitted				Was	Water Well Dis	infected?	YES	NO
5 TYPE OF CA	SING USED:	5. Wrought	iron	7. Fiberglass	9. 0	Other (Speci	fv below) CA	ASING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SR)		· ·	C.D.	R-26	, ,		Welded	Clamped
2. PVC	4. ABS	6. Asbestos	-Cement	8. Concrete t	ile SD	-Z0				
Blank casing diamet	er 5 i	n. to 4	40 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height abov	e land surface:	12 in		Weight:	2.35	lbs. / ft.	Wall	thickness or gaug	ge No214	1
	OR PERFORATION			rroigin.		100.711.	*****	thickness of gaug	214	
1	3. Stainless Steel	5. Fiberglass		7. PVC	9. /	ABS	11. (Other (specify)		
	4. Galvanized	6. Concrete Ti	le 8	B. RMP (SR)	10	Asbestos-Ce		None used (open	hole)	
				J. 141111 (O14)	10.7	13003103-06	smont 12.7	tone doca (open	noic)	
	DRATION OPENING									
1. Continuous slo	t 3. Mill slo	t 5. G	auzed wrap	oped	7. To	7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutt	er 4. Key pu	nched 6. W	/ire wrappe	d	(8. S .	aw cut	10. Ot	her (specify)		
SCREEN - PERFOR	ATION INTERVAL	From	40 ft.	. to	94	ft.,	From			
OOKEEN PERIOR	ATTOMINTERVAL					,		ft.	to	ft.
		From	ft.			ft.,	From	ft.	to	ft.
GRAVEL PA	ACK INTERVALS:	From	24 ft.	to	94	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATER	IALS: 1. Neat c	ement	2. Cemen	t Grout		3. Bentonit	•	Other hent	onite hole pl	110
Grout Intervals:	From 4	ft. to	24 ft		ft.		ft.,	From	ft. to	ug ft.
What is the nearest s		ntamination:	,	_			н.,	FIOIII	11. 10	π.
1. Septic tank	4. Lateral	lines 7.	Pit privy	1	10. Livesto	ck pens	13. Inse d	ticide storage	15. Oil well/	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel st						rage 14. Abandon water well 16. Other (specify below)				
3. Watertight sew	er line 6. Seepag	e nit 9.	Feed yard		12. Fertilize	r storage				
Direction from well?	East	o pit	,				How r	nany feet? 10 f	t. plus	
From To		ITHOLOGIC	LOG		From	То	1		GIC LOG	
0 3	topsoil		LOO		110111	 		LITTIOLO	GIC LOG	
3 8	clav	······································			1					
8 62	brown shale									
62 94	grey shale									
					<u> </u>					
					1					
7 Contractor's or	Landowner's Certifica	ation: This water v	vell was 1.	constructed	2. re	constructe	ed or 3.	plugged	ınder my jurisdic	tion and
was completed on	(mo/day/year)	7/10/2014	an	nd this record	is true to the	e best of my	knowledge and	l belief.		
						•	-		12011	
	Contractor's License				en record wa	as complete	d on (mo/day/ye		/2014	
under the business	name of Harp V	Vell and Pum	p Service	e	by (s	ignature)	T	<u>odd S</u>	Harr)
	-								. ,	•