WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SW NW NW SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NW 9 20 ME Т 27 S **2E** E/W 1/4 1/4 R Distance and direction from nearest town or city street address of well if located within city? 10401 E. Summer Field Circle Wichita, Kansas **NIES CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303 CITY, STATE Wichita, Kansas ZIP CODE: Application Number: 75 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft 40 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: gpm Pump test data: Well water was ft. after hours of pumping @ NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm apm 12 to 75 ً Bore Hole Diameter in. ft. and to WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 1. Lawn and garden only 9₩ SE 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) NO submitted Was Water Well Disinfected? TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 40 ft. in. to ft.. Dia. in to ft.. Dia in to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 8. RMP (SR) 2. Brass 12. None used (open hole) 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7 Torch cut 2. Louvered shutter 8. Saw cut 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 40 ft., From to From ft to ft. ft. From to ft., From ft ft tο 24 **75 GRAVEL PACK INTERVALS:** ft. to From From ft to ft. ft. From to ft.. From ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 24 From ft.. From ft. ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit West How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τо 0 3 topsoil 3 20 clav 20 70 grey shale 70 75 limestone under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or plugged

8/26/2014 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year)

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

8/27/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb