WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE NE 1/4 NE 11 27 1/4 1/4 Т S 2E E/W Distance and direction from nearest town or city street address of well if located within city? 1946 N. Split Rail Ct. Wichita, Kansas FAHSHOLTZ CONSTRUCTION 2 WATER WELL OWNER: Board of Agriculture, Division of Water Resource "RR#,ST. ADDRESS,BOX #: 11927 E. Shannon Way Ct. Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 85 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. ELEVATION: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 65 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/28/14 Pump test data Well water was ft. after hours of pumping @ NW NFapm Est. Yield: apm Well water was ft. after hours of pumping @ Φ gpm 12 to 85 Ξ Bore Hole Diameter in and ft. WELL WATER TO BE USED AS: 11. Injection well 5. Public water supply 7. Lawn and garden only SW SE-3. Feedlot 1 Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) NO 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS 5 Blank casing diameter 45 Dia. ft., Dia in. ft. to 12 Casing height above land surface: Weight: 2.35 in.. lbs / ft Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 2 Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 ft 85 From to ft., From ft. ft to ft From to ft., From ft. to **GRAVEL PACK INTERVALS:** 24 ft. to 85 From ft., From ft. From ft. to ft.. From ft to ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft., ft. From to ft ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit Direction from well? East How many feet? 10 ft. plus LITHOLOGIC LOG From Тο From To LITHOLOGIC LOG topsoil 10 clay 10 80 grey shale 80 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and 7/28/2014 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/30/2014 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)