WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION RANGE NUMBER Sedgwick SE NE 11 27 1/4 Т S **2E** R Ε/W Distance and direction from nearest town or city street address of well if located within city? 1812 N. Split Rail Circle Wichita, Kansas DAVIS, Carolyn WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1812 N. Split Rail Circle CITY, STATE: Wichita, Kansas ZIP CODE Application Number: 92 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION ft. **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: fŧ WELL'S STATIC WATER LEVEL 45 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/28/14 Pump test data: Well water was ft. after hours of pumping @ NW NE. gpm Est. Yield: ft. after apm Well water was hours of pumping @ gpm ≌ 12 to 92 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 40 Dia. to ft.. in. to Dia in. ft. 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2 Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 40 ft. From to ft., From to ft. From ft. to ft., From ft ft. 24 **GRAVEL PACK INTERVALS:** ft. to 92 From ft.. From ft. ft. From to ft.. From ft to **GROUT MATERIALS** Other 2. Cement Grout bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: ft. 24 From ft.. From tο ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit West How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG From Τо From LITHOLOGIC LOG To Λ topsoil clav 8 88 gray shale 88 92 limestone

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 7/28/2014 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/30/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb