WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION RANGE NUMBER Sedgwick NE NW 35 27 2E 1/4 Т S R Ε/W Distance and direction from nearest town or city street address of well if located within city? 13517 Mustang Ct. Wichita, Kansas KLAYSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX # 10008 W.York CITY, STATE Wichita, Kansas ZIP CODE: Application Number 4 DEPTH OF COMPLETED WELL: 114 **ELEVATION:** LOCATE WELL'S LOCATION ft. WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/26/14 Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm Ξ 12 to 114 Bore Hole Diameter in. ft. to WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 50 Blank casing diameter Dia. to in to ft. Dia in. ft. to 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1 Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 1. Continuous slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 2. Louvered shutter 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 ft From to ft.. From ft to ft. From ft to ft., From ft. ft. **GRAVEL PACK INTERVALS:** 24 ft. From 114 ft.. From ft to ft. ft. From to ft., From ft. **GROUT MATERIALS:** 6 Other 1. Neat cement 2. Cement Grout bentonite hole plug 3. Bentonite Grout Intervals: ft. 24 From ft.. From ft., From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North How many feet? 20 ft. plus Direction from well? LITHOLOGIC LOG From Τо From To LITHOLOGIC LOG 3 O topsoil 20 clay 20 114 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and

was completed on (mo/day/year) 7/26/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/28/2014

under the business name of Harp Well and Pump Service by (signature) Todd S. Horb