


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Butler	FRACTION NW 1/4 SW 1/4 SE 1/4	SECTION NUMBER 17	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 3E E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

613 Lakecrest Circle Andover, Kansas

2 WATER WELL OWNER: H & H HOMEBUILDERS INC.	Board of Agriculture, Division of Water Resource
RR#.ST. ADDRESS,BOX #: 3906 N. lakecrest	Application Number:
CITY, STATE: Wichita, Kansas	ZIP CODE:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION:
	Depth of groundwater Encountered: _____ ft.
	WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 10/7/14
	Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm
	Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm
	Bore Hole Diameter 12 in. to 95 ft. and _____ in. to _____ ft.
	WELL WATER TO BE USED AS:
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted
	Was Water Well Disinfected? YES NO

5 TYPE OF CASING USED:	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS: Glued Threaded		
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded Clamped		
Blank casing diameter	5 in.	to	45 ft.,	Dia.	in.	to	ft.	
Casing height above land surface:	12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.	.214			
TYPE OF SCREEN OR PERFORATION MATERIAL:	1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)		
	2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
	2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)			
SCREEN - PERFORATION INTERVAL	From	45 ft.	to	95 ft.,	From	ft.	to	ft.
					From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	to	95 ft.,	From	ft.	to	ft.
					From	ft.	to	ft.

6 GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other bentonite hole plug
Grout Intervals:	From 4 ft.	to 24 ft.,	From	ft. to
What is the nearest source of possible contamination:	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage
Direction from well?	East			How many feet? 10 ft. plus

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	8	clay			
8	90	gray shale			
90	95	limestone			

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/7/14 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/10/2014
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp