	WATER W	VELL RECORD	Form WV	VC-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL:	FRACTION					P NUMBER	RANGE NUMBER	
Sedgwick	SE 1/4		1/4	15	Т 2	7 s	R 2E	E/W
Distance and direction from nearest to 12241 E. Troon Ct.	· · · · · · · · · · · · · · · · · · ·	chita, Kansas						
2 WATER WELL OWNER:		CONSTRUCTION						
RR#,ST. ADDRESS,BOX #:	Board of Agriculture, Division of Water Resource							
CITY, STATE:	Wichita, Kansas		Z	P CODE:		Application Num	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COM	PLETED WELL:	67 ft.		ELEVATION:			
N N	Depth of groundwate		ft			ft.		ft.
	WELL'S STATIC W	ATER LEVEL 38	FT. BELC	W LAND SU	JRFACE MEASI	JRED ON mo/o	lay/yr: 10/24	/14
NW NE			vater was		ft. after		of pumping @	gpm
w William	Est. Yield: E Bore Hole Diamete	1.0	vater was to	5 7 ft.	ft. after		of pumping @	gpm
2 w	WELL WATER TO		ιο •	J <i>i</i> II.	and	in.	to na 11. Injec	ft. tion well
SW SE			vater supply	7. Lawn a	and garden only	⊳ ^{9. Dewaterii}	12. Other (Sp	
	1 1		water supply	8. Air cor		10. Monitorin	ng well	,
S	Was a chemical/bact submitted	leriological sample submitted	o Department?	YES Was V	NO Vater Well Disin		what mo/day/yr wa	as sample O
5 TYPE OF CASING USE	n·	7.5:5	9.0	ther (Specify		SING JOINTS: (Glued	Threaded
1. Steel 3.	RPM (SR) 5. Wrough		S.D.	R-26	, below,	5.11.0 BO.11.10.	Welded	Clamped
2. PVC 4.	ABS	os-Cement 8. Concrete	e tile SD	IX-20				·
Blank casing diameter	5 in. to	35 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surfa	•	Weight:	2.35 I	bs. / ft.	Wall th	ickness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION O		(-	,			` '	,	
		Gauzed wrapped	7. T o	rch cut	9. Dril l	led holes	11. None (o _l	pen hole)
2. Louvered shutter	4. Key punched 6.	Wire wrapped	(8. Sa	w cut	10. Oth	er (specify)		
SCREEN - PERFORATION INT	••	35 ft.	to 67					
SCREEN - PERFORATION INT	ERVAL From From	ss it.	to U7	ft., ft.,	From From	ft.	to	ft.
GRAVEL PACK INTER		24 ft.	to 67	ft.,	From	ft. ft.	to	ft.
GIVALET MORNITER	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS:							onite hole plu	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to					ft.,	From	ft. to	ಕ ft.
What is the nearest source of po	ossible contamination:	,						
1. Septic tank 4. Lateral lines			10. Livestoo	•		13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)		
2. Sewer lines 5. Cess Pool								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? East How many feet? 10 ft. plus								
From To	LITHOLOGI	IC LOG	From	То	11000 1110		GIC LOG	
0 3 topsoil								
3 8 clay			<u> </u>					
8 67 gray st	ıale							
								····
							*.W.	
			_					
7 Contractor's or Landowne	r's Certification: This wate	er well was 1. construct	ed 2. re	constructed	d or 3,	plugged	under my jurisdictio	on and
was completed on (mo/day/ye	ear) 10/24/201	4 and this reco	rd is true to the	e best of my	knowledge and	belief.		
Kansas Water Well Contracto	or's License No. 236			•	l on (mo/day/yea		7/2014	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb								