WATE	R WFI	LL RECORD	SW NE S Form W	W 5E WC-5	Dis	vision of Wate	r Pesources Ann N			
WATER WELL RECORD 1 LOCATION OF WATER WELL:					Division of Water Resources App. No. Section Number Township No. Range Number					
Cour	ity: Sed	awick	1/4 1/4	0 1/4 88 1/4		34	T 27 S	R 2 ☑ E □W		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						Global Positioning System (GPS) information: Latitude: (in decimal degrees) Longitude: (in decimal degrees) Elevation: Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: Victoria Homes						1: WGS 8- ction Method:	4, □ NAD 83, □	NAD 27		
•	RR#, Street Address, Box #: 13533 E. Mount Vernon Ct					GPS unit (Make/Model:)				
	City, State, ZIP Code : Wichita, KS 67230						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
	3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 100 ft.									
	ECTION BOX: Depth(s) Groundwater Encountered (1).40									
	Pump test data: Well water wasft. after hours pumping gp									
w NV										
-	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
sv	□ Domestic □ Feedlot □ Oil field water supply □ Dewatering □ Other (Specify below) □ Irrigation □ Industrial □ Domestic-lawn & garden □ Monitoring well									
	s If yes, mo/day/yr sample was submitted									
was submitted Water well disinfected?										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: 🗹 Glued 🔲 Clamped 📋 Welded 📋 Threaded										
Casing diameter .5 in. to .100 ft., Diameter in. to ft., Diameter ft.										
Casing height above land surface. 12 in., Weight 2.5 lbs./ft., Wall thickness or gauge No. SDR26										
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel										
Brass Galvanized Steel None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 49										
From										
GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From ft. to ft.										
From ft. to ft., From ft. to ft.										
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other										
Grout Intervals: From .3										
What is the nearest source of possible contamination: □ Septic tank □ Lateral lines □ Pit privy □ Livestock pens □ Insecticide storage □ Other (specify below)										
	Sewer lines									
		ht sewer lines	it Feedyard	Fertilizer s		Oil well/ga		······································		
FROM	TO TO	n well East LITHOLOG	ICLOC	FROM	TO We			IGGING INTERVALS		
0	3	Topsoil	IC LOG	TROM	10	LITHO. LC	od (cont.) or FLO	GGING INTERVALS		
3	30	Clay								
30	100	Limestone								
ļ				<u> </u>						
			71.1	 						
				-						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .11/6/2014 and this record is true to the best of my knowledge and belief.										
Kaneae	y JUFISOIO Water W	ction and was completed of ell Contractor's License N	n (mo/day/year) .1.!!?!	Vater Well D	ecord w	as completed	o the best of my K on (mo/day/year)	11/7/2014		
under th	e busine	ss name of Premier Pun	np & Well Service. In	C	bv (si	ignature	Divoers	نسواراها		
INSTRUC	CTIONS:	Use typewriter or ball point pen	. PLEASE PRESS FIRMLY	and <u>PRINT</u> cl	early. Plea	ase fill in blanks	and check the correct	answers. Send one copy to		
 Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at 										