WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: TOWNSHIP NUMBER RANGE NUMBER FRACTION SECTION NUMBER Sedgwick NE NE 27 1/4 11 Т S R **2E** Ε/W Distance and direction from nearest town or city street address of well if located within city? 1918 N. Burning Tree Wichita, Kansas **NIES CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX # 10233 E. 21st N. #303 Wichita, Kansas ZIP CODE: 67206 CITY, STATE: Application Number: 86 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/25/15 Pump test data: Well water was ft. after hours of pumping @ gpm **₩**₩ X Est. Yield: Well water was ft. after hours of pumping @ apm gpm Φ 12 to 86 ≌ Bore Hole Diameter in. ft. and in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only 3₩ - SE-1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 40 Dia. in. to in ft.. Dia. to ft. 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 2. Louvered shutter 6. Wire wrapped 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 40 86 From to ft., From ft. From to ft.. From ft. ft. **GRAVEL PACK INTERVALS:** 24 ft. to 86 From ft., From ft to ft. From ft. to ft. From ft. **GROUT MATERIALS:** 6 Other 1. Neat cement 2. Cement Grout bentonite hole plug 3. Bentonite Grout Intervals: From 24 ft.. From From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit East How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τо 3 topsoil Q clay 80 grev shale 80 86 limestone under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or plugged was completed on (mo/day/year) 3/25/2015 and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 3/26/2015 Kansas Water Well Contractor's License No. 236

by (signature)

under the business name of Harp Well and Pump Service

Todd S. Harb