WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NW1/4 NWSE 1/4 12 27 2E1/4 Т S R E/W Distance and direction from nearest town or city street address of well if located within city? 15211 E. Summerfield Wichita, Kansas **NIES CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10333 E. 21st St N. Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 116 ft. ELEVATION: ft. Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 46 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/20/15 Pumo test data: Well water was ft, after hours of pumping @ NW · NE apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ξ۷ Bore Hole Diameter 12 to 116 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample s Was a chemical/bacteriological sample submitted to Department? (NO) submitted YES Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped **SDR-26** 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 50 ft.. Dia. ft.. to to Dia in. ft. 12 Casing height above land surface: Weight: 2.35 Wall thickness or gauge No. lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 50 116 From to ft.. From ft. to From ft. to ft.. From ft. ft. GRAVEL PACK INTERVALS: 24 ft. 116 From ft.. From ft ft. ft. From to ft., From ft. to ft **GROUT MATERIALS** Other 2. Cement Grout bentonite hole plug 1. Neat cement 3 Bentonite Grout Intervals: From 4 ft. 24 ft.. From to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 11. Fuel storage 16. Other (specify below) 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line West How many feet? 20 ft. plus Direction from well? From Τо LITHOLOGIC LOG From То LITHOLOGIC LOG 0 3 topsoil 18 3 clay 18 114 gray shale 114 116 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and

was completed on (mo/day/year)	10-20-2015	and this record is true to the best of my knowledg	e and belief.
Kansas Water Well Contractor's License	e No. 236	This water well record was completed on (mo/o	day/year) 10-21-2015
under the business name of Harp V	Vell and Pump Servi	ice by (signature)	Todd S. Harp