Form WWC-5 KSA 82a-1212 WATER WELL RECORD LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE 1/4 NESE 1/4 4 Т 27 S 2E R F/W Distance and direction from nearest town or city street address of well if located within city? 2413 N. Greenwich Rd. Wichita, Kansas WATER WELL OWNER: REGENCEY LAKES RETAIL Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2413 N. Greenwich Rd. CITY, STATE Wichita, Kansas ZIP CODE Application Number: 95 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. N ft WELL'S STATIC WATER LEVEL 34 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/2/15 Pump test data: Well water was NW NE ft. after hours of pumping @ qpm Est. Yield: apm Well water was ft. after hours of pumping @ gpm ≌ Bore Hole Diameter 12 95 in. fŧ WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SE 5. Public water supply 7. Lawn and garden only SW 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) s submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4 ABS Blank casing diameter 45 Dia. in. to ft., Dia. in to ft 12 Casing height above land surface: in 2.35 Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9 ABS 2. Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 95 From to ft From to ft. ft. From to ft.. From ft tο ft. 24 GRAVEL PACK INTERVALS: ft. 95 From ta ft., From to ft ft. From to ft From ft. ft. GROUT MATERIALS: Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft., From ft to ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit Direction from well? South How many feet? 70 ft. plus From Τо LITHOLOGIC LOG From To LITHOLOGIC LOG topsoil clay 15 90 grey shale 90 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, under my jurisdiction and 9/2/2015 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/4/2015 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb