WAT	TER WELL RECORI	D Fo	orm WW	/C-5 k	(SA 82a-1	212			
LOCATION OF WATER WELL: FRACTION				ION NUMBE					
			1/4	11	T 27 S R			E E/W	
Distance and direction from nearest town or city street add	ress of well if located within city?		· · · · · · · · · · · · · · · · · · ·						
	iita, Kansas								
	STRUCTION					Board of Ami	aultura Division of l	Matas Danas	
	1st N. Ste. 303					Board of Agri	culture, Division of \	water Resource	
CITY, STATE: Wichita, K		0.4		CODE:		Application Num	nber:		
3 LOCATE WELL'S LOCATION 4 DEPTH (OF COMPLETING OF ELL:	84	ft.		ELEVATION	l:			
	oundwater Encountered:		ft.			ft.		ft.	
	ATIC WATER LEVEL	45	FT. BELO	W LAND S	URFACE MEA	SURED ON mo/d	lay/yr: 6/1 9	9/15	
NW NE		Weil water			ft. after		of pumping @	gpm	
Est. Yi	51	Well wate			ft. after		of pumping @	gpm	
	Diameter in. FER WAS USED AS:		to	f	t. and	in.	to	ft.	
1. Domes		ıblic wate	r supply ^c	7. Lawn	and garden o	9. Dewaterii	· · ·	ction well pecify below)	
2. Irrigati					nditioning	10. Monitorin		pecity below)	
	nical/bacteriological sample subn			YES	NO	-	vhat mo/day/yr	•	
submitted				Was	Water Well Dis	sinfected?	YES	NO	
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5.	Wrought Iron 7. Fib	erglass	9. Otl	ner (Specif	y below) C	ASING JOINTS:	Glued	Threaded	
	Asbestos-Cement 8. Con	ncrete tile					Welded	Clamped	
Blank casing diameter 5 in.	to ft., [Dia.	in.	to	ft.,	Dia. i	n. to	ft.	
Casing height contained surface: 36	,						-	п.	
TYPE OF SCREEN OR PERFORATION MATER	in., Weig	grit.	ID	s. / ft.	vvaii	thickness or gaug	je No.		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC				9. ABS 11. Other (specify) N/A					
·	oncrete Tile 8. RMF	P (SR)	10. As	bestos-Ce		None used (open			
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped			7. Tor	7. Torch cut 9. Drilled holes 11. None (open hole)				open hole)	
2. Louvered shutter 4. Key punched	6. Wire wrapped		8. Sav	v cut	10. O	ther (specify) N_{ℓ}	'A		
SCREEN - PERFORATION INTERVAL Fro		to		ft.,	From	ft.	to	ft.	
Fro		to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS: Fro	om ft.	to		ft.,	From	ft.	to	ft.	
Fro	om ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement	2. Cement Gro	ut	3.	Bentonite	e	Other bent	onite hole p	lug	
Grout Intervals: From 3 ft.	to 23 ft.,	From	ft.	to	ft.,	From	ft. to	ft.	
What is the nearest source of possible contaminations 1. Septic tank 4. Lateral lines	tion: 7. Pit privy	10.	Livestock	pens	13. Inse	cticide storage	15. Oil well/0	Gas well	
	8. Sewage lagoon	11	. Fuel stor	age		ndon water well		pecify below)	
2. Sewer lines 5. Cess Pool	9. Feed yard		Fertilizer	-	14. Apa	ndon water wen	``	,	
Watertight sewer line 6. Seepage pit Direction from well?	5. Feed yalu	12	. reitinzei	storage	How	many feet?			
	LOGIC LOG		From	То	11011	LITHOLO	GICLOG		
1011110	20010 200		0	3	compacte		OIO LOO		
			3	23		hole plug			
			23	84	chlorinate	1 0		******	
								** * * * * * * * * * * * * * * * * * * *	
		+							
		+			 			***********	
		+							
7 Contractor's or Landowner's Certification: T	hie water well was 4		2	one44-	d 02 0 /	nlunged	Inder my hardedter	lion and	
	0.2015			onstructe			under my jurisdic	IOH AND	
was completed on (mo/day/year) 0-1	and this	record is	true to the	pest of my	knowledge an	a peliet.			

y/year) 6/21/2015 Todd S. Harp Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)