		WATER W	ELL RECO	DRD F	orm WV	VC-5 K	(SA 82a-1	1212				
1 LOCATION OF WATE	R WELL:	FRACTION				TION NUMBE	R TOWN:	SHIP NUMBER	RAN	RANGE NUMBER		
Sedgwick Distance and direction from	om nearest town or city	SE 1/4			1/4	12	<u> </u>	27 S	R	<u> 2E</u>	Ε/W	
15627 E. Roc	-		ita, Kansas	City:								
2 WATER WELL	OWNER: SHA	RP HOMES							7.5			
RR#,ST. ADDRESS,BOX #: 2131 N. Collective Ste. #4											er Resource	
		hita, Kansas		10	^	P CODE:		Application I	Number:			
3 LOCATE WELL'S LO WITH AN "X" IN SE	CTION BOX:	DEPTH OF COM					ELEVATIO	N:				
N N		epth of groundwate			ft			ft.			ft.	
	' ! !	ELL'S STATIC W		42		W LAND S		ASURED ON m		5/6/1	-	
do NW	NE.	Est. Yield:	ımp test data: gpm	Well wate			ft. after ft. after		urs of pumping ours of pumping	_	gpm	
W Mile	X B	Bore Hole Diamete		in.	to 1	1 20 ft		in.		to	gpm ft.	
-		ELL WATER TO						9. Dewat	ering 11	. Injecti	on well	
sw							and garden o			er (Spe	cify below)	
	i	2. Irrigation 4 Was a chemical/bacte	. Industrial 6 eriological sample:			8. AIF COI	nditioning NO	10. Monito ; If ye	s, what mo/day	//yr was	s sample	
		ıbmitted					Water Well Di	sinfected?	YES	NO	,	
5 TYPE OF CAS		5. Wrough	t Iron 7.	Fiberglass	9. O	ther (Specify	y below)	CASING JOINTS	S: Glued	Т	hreaded	
1. Steel	3. RPM (SI > 4. ABS	6. Asbesto	s-Cement 8.	Concrete til	e SDI	R-26			Welded	C	Clamped	
Blank casing diamet	_	in. to	50 ft.,	Dia.	in.	to	ft.,	Dia.	in. to		ft.	
1		12 in									11.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:												
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)												
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
1. Continuous slo	t 3. Mill sl	ot 5.	Gauzed wrapp	ed	7. To	rch cut	9. 🖸	rilled holes	11. No	ne (ope	en hole)	
2. Louvered shutte	er 4. Key p	unched 6.	Wire wrapped		(8. Sa	w cut	10. (Other (specify)				
SCREEN - PERFORA	ATION INTERVAL	From	50 ft.	to	120	ft.,	From	ft.	to)	ft.	
		From	ft.	to		ft.,	From	ft.	to)	ft.	
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	120	ft.,	From	ft.	to	נ	ft.	
		From	ft.	to		ft.,	From	ft.	to)	ft.	
6 GROUT MATER	IALS: 1. Neat	cement	2. Cement	Grout	3	B. Bentonite	•	Other be	ntonite hol	e plug		
Grout Intervals: From 4 ft. to 24 ft., From					ft. to		ft.,	From	ft.	to	ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy					D. Livestoc	k pens	13. Insecticide storage 15. Oil well/Gas			s well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (s								r (spec	ify below)			
3. Watertight sew	er line 6. Seepa	ige pit	Feed yard	1.	2. Fertilize	r storage						
Direction from well? Northeast							How many feet? 50 ft. plus					
From To		LITHOLOGI	C LOG		From	То		LITHOL	LOGIC LO	3		
3 35	topsoil clay											
35 60	brown shale											
60 110	gray shale					-						
110 120	limestone											
	 					-						
						-						
7 Contractor's or	Landowner's Certifi	ication: This water	well was 4	onetructod) a ==	construct	1 01 3	nluaged	under my in	isdiction	and	
_		5/6/16				constructed		plugged	under my jur	iaulctior	i and	
was completed on						-	knowledge ar		5/0/1 <i>/</i>			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/9/16												
under the business	name of Harp	Well and Pur	mp Service		by (si	gnature)		Todd	S. Ha	rh		