WATER WELL RE	CORD Form WV	VC-5 KSA 8	2a-1212	
1 LOCATION OF WATER WELL: FRACTION	SEC	TION NUMBER T	OWNSHIP NUMBER	RANGE NUMBER
Sedgwick NE 1/4 NE	1/4 SE 1/4	2	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located with	•			
	, Kansas			
2 WATER WELL OWNER: RISHEL, Richard			Board of Agri	culture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 2518 N. Springdale Circle				
CITY, STATE: Wichita, Kansas		P CODE:	Application Nun	nber:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	ELL: 100 ft.	ELEV	ATION:	
N Depth of groundwater Encounte			ft.	ft.
WELL'S STATIC WATER LEVE	EL 42 FT. BELO	W LAND SURFACE	E MEASURED ON mo/o	day/yr: 6/23/16
Pump test dat	a: Well water was			of pumping @ gpm
Est. Yield: gpm  Bore Hole Diameter 12	Well water was			s of pumping @ gpm
		.00 ft.	and in.	to ft.
9. Dewatering				
1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well				
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample				
submitted Was Water Well Disinfected? YES NO				
5 TYPE OF CASING USED: 5. Wrought Iron	7. Fiberglass 9. O	ther (Specify below)	CASING JOINTS: (	Glued Threaded
1. Steel 3. RPM (SR) Welded Clamped				
2. PVC 4. ABS 6. Asbestos-Cement	8. Concrete tile			
Blank casing diameter 5 in. to 50 ft.,	Dia, in.	to ft	t., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wr	apped 7. To	rch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapp	ped 8. Sa	w cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 50	ft. to 100	ft., Fro	om ft.	to ft.
From	ft. to	ft., Fro	om ft.	to ft.
GRAVEL PACK INTERVALS: From 24	ft. to 100	ft., Fro	m ft.	to ft.
From	ft. to	ft., Fro	om ft.	to ft.
1. Neat cement 2. Cent	_	3. Bentonite		onite hole plug
What is the nearest source of possible contamination:	t., From ft.	to	ft., From	ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestoc	k pens 13	3. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage				
Direction from well? South & West			How many feet? 10 f	ft. plus
From To LITHOLOGIC LOG	From	То	LITHOLO	GIC LOG
0 3 topsoil				
3 28 clay			W-0.4-0	
28 60 brown shale 60 95 gray shale				
60 95 gray shale 95 100 limestone				
73 TW IIIIESIOTE				
		<del>                                     </del>		
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and				
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/27/16				
	This water well record wa	s completed on (mo	oldaylyear) 6/2 Todd S	