WATER WELL RECORD Form WWC-5 KSA 82a-1212											
1'1	ON OF WATE	R WELL:	FRACTION	PIE.			CTION NUMBE	1	IP NUMBER	1	NUMBER
	wick			/4 NE	1/4 NI	E 1/4	11	T 2	27 s	R 2	E E/W
Distance and direction from nearest town or city street address of well if located within city? 14201 E. Churchill St. Wichita, Kansas											
2 WATER WELL OWNER: FAHSHOLTZ CONSTRUCTION											
	RR#,ST. ADDRESS,BOX #: P.O.Box 818										
	CITY,	STATE: And	dover, Kansa	iS			ZIP CODE:		Application Nur	nber:	
3 LOCAT	TE WELL'S LO		DEPTH OF CO	MPLETED V	NELL:	86 f	t.	ELEVATION:			
WITH	AN "X" IN SEC N		– Depth of groundwa	iter Encount	ered:		ft.		ft.		ft.
	1	V	WELL'S STATIC \	NATER LEV	/EL 28	FT. BE	OW LAND S	URFACE MEAS	URED ON mo/o	day/yr: 2 /1	19/16
-	-NW	NE-X	ı	Pump test da	ata: Well	water was		ft. after	hours	of pumping @	gpm
M Mile		' 	Est. Yield:	gpm		water was		ft. after	hours	s of pumping @	gpm
		' i I	Bore Hole Diame	_	2 in.	to	86 fi	t, and	in.	to	ft.
T	sw	SE	WELL WATER TO 1. Domestic	3. Feedlot		water suppl	v <7. Lawn	and garden on	9. Dewateri	9	ection well
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
'	S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample										
			submitted				Was	Water Well Disir	nfected?	YES	NO
\Box		SING USED:	5. Wroug	ght Iron	7. Fibergla	ıss 9.	Other (Specif	fy below) CA	SING JOINTS: (Glued	Threaded
1. Steel 3. RPM (SR) 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped											
	sing diamete		in. to	40 ft		in.	to	ft.,	Dia.	in. to	ft.
1	_	_	10	40 10				,			
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)											open hole)
2. Louv	ered shutte	er 4. Kevi		6. Wire wrap	• •		Saw cut		ner (specify)		
			•			_					
SCREEN	- PERFURA	ATION INTERVAL		40	ft. ft.	to 86	ft.,	From	ft.	to	ft.
	מסאיבו פא	CK INTERVALS:	From	24	π. ft.	to 86	ft.,	From	ft.	to	ft.
	NAVEL FA	CK INTERVALS.	From	24			ft.,	From	ft.	to	ft.
- 1 000			From		ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug											lug
	Intervals: e nearest so	From 4 ource of possible of	-	o 24	ft., From	1	ft. to	ft.,	From	ft. to	o ft.
1. Septi		4. Later		7. Pit privy	y	10. Livest	ock pens	13. Insect	icide storage	15. Oil well	Gas well
2. Sewe	er lines	5. Cess	Pool	8. Sewage	lagoon	11. Fuel s	torage	14. Aband	on water well	16. Other (s	pecify below)
3. Wate	rtight sewe	r line 6. Seep	age pit	9. Feed ya	rd	12. Fertili:	zer storage			Non	e Yet
	from well?							How m	any feet?		
From	To		LITHOLOG	IC LOG		From	1 To		LITHOLO	GIC LOG	
0	3	topsoil							1400-1		
8	20	clay brown shale								***	
20	80	gray shale		-			1	- · · · - · ·		1.04	1.177
80		limestone									
<u> </u>							_				
										·····	
7						\dashv		<u> </u>			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and											
was completed on (mo/day/year) 2/19/2016 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/22/2016											
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb											