Form WWC-5 KSA 82a-1212 WATER WELL RECORD 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SWSedgwick $\mathbf{s}\mathbf{w}$ 27 2ENE 11 Т R E/W 1/4 1/4 1/4 S Distance and direction from nearest town or city street address of well if located within city? 1803 N. Burning Tree Circle Wichita, Kansas WATER WELL OWNER: ROBL CONSTRUCTION Board of Agriculture, Division of Water Resource 5842 W. 21st N. RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE ZIP CODE: Application Number 84 **ELEVATION:** LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. WITH AN "X" IN SECTION BOX: ft. ft. ft. Depth of groundwater Encountered: 28 2/19/16 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm <u>a</u> map ≌ 12 84 Bore Hole Diameter to and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO S YES submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Clamped Welded SDR-26 Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 40 Dia. Dia. to in. ft. to Casing height above land surface: 2.35 in. Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 40 From ft ft., From to ft. to ft From to ft., From to ft. 24 GRAVEL PACK INTERVALS: ft. to 84 From ft., From ft. From ft. to ft.. From ft ft. to **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft., ft. ft. From ft. to What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit East Direction from well? How many feet? 50 ft. plus From Τо LITHOLOGIC LOG From To LITHOLOGIC LOG topsoil 3 8 clav 8 80 grey shale 80 84 limestone Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 2/19/2016 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 2/22/2016 Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) by (signature) Todd S. Harb under the business name of Harp Well and Pump Service