WATER WELL RECORD	Form WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NW 1/4 NW 1/4 SE	1/4 12	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?			
10502 E. Summerfield Circle Wichita, Kansas			
2 WATER WELL OWNER: RITCHIE BUILDING		Board of Agr	iculture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N. Bldg. 1000 CITY, STATE: Wichita, Kansas	710 0005	Application Nur	mh ar:
	ZIP CODE:	Application Nur ELEVATION:	niber.
WITH AN "X" IN SECTION BOX:			4
Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 28		JRFACE MEASURED ON mo/	
Pump test data: Well wa			s of pumping @ gpm
Est. Yield: gpm Well was Bore Hole Diameter 12 in.	iter was to 83 ft.		s of pumping @ gpm to ft.
WELL WATER TO BE USED AS:	10 63 11.		44 (-141
	ter supply 7. Lawn a	and garden only 9. Dewater	12. Other (Specify below)
1	vater supply 8. Air con	nditioning 10. Monitori	ng well
S Was a chemical/bacteriological sample submitted to	Department? YES	NO ; If yes,	what mo/day/yr was sample
submitted	Was V	Vater Well Disinfected?	YES NO
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	Other (Specify	below) CASING JOINTS:	Glued Threaded
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete 6	ile SDR-26		Welded Clamped
Blank casing diameter 5 in. to 43 ft., Dia.		ft., Dia.	in. to ft.
	in. to		
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer		hole)
	TO: Addedios-Get	nem 12. Hone about (open	
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7 Touch and	O Drillad halas	11. None (open hole)
	7. Torch cut	9. Drilled holes	11. None (open noie)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 43 ft. to	83 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	9 83 ft.,	From ft.	to ft.
From ft. to	o ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout			onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	3. Bentonite	beni	ft, to ft.
What is the nearest source of possible contamination:	ft. to	ft., From	
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? South		How many feet? 50	
From To LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG
0 3 topsoil			
3 17 clay 17 55 brown shale			W-W
17 55 brown shale 55 83 grey shale	 	- A. s. Mar.	
55 Bicy strate			
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2 reconstructed	or 3. plugged	under my jurisdiction and
was completed on (mo/day/year) 2/26/2016 and this record is true to the best of my knowledge and belief.			
			_
under the business name of Harp Well and Pump Service by (signature) Todd S. Horp			