	WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER	
Sedgwick	NW 1/4 NW 1/4 SE	1/4 12	T 27 S	R 2E E/W	
Distance and direction from nearest town or city	street address of well if located within city?		•		
15220 Summerfield	Wichita, Kansas				
	S CONSTRUCTION				
	3 E. 21st N. SE#303		Board of Agr	iculture, Division of Water Resource	
	hita, Kansas	ZIP CODE:	Application Nur	nber:	
	DEPTH OF COMPLETED WELL: 120		ELEVATION:		
WITH AN "X" IN SECTION BOX:				6	
	pth of groundwater Encountered:	ft.	ft.	ft.	
WE	ELL'S STATIC WATER LEVEL 38		RFACE MEASURED ON mo/	day/yr: 7/12/16	
NWNE	Pump test data: Well wate	er was	ft. after hours	s of pumping @ gpm	
	Est. Yield: gpm Well wate		ft. after hours	s of pumping @ gpm	
	ore Hole Diameter 12 in.	to 120 ft.	and in.	to ft.	
	ELL WATER TO BE USED AS:		9. Dewateri	ing 11. Injection well	
	12. Other (Specily Below)				
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well				
, v i	Vas a chemical/bacteriological sample submitted to D			what mo/day/yr was sample	
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded					
	6. Asbestos-Cement 8. Concrete til	SDR-26		Welded Clamped	
2. PVC 4. ABS			<i>.</i>		
Blank casing diameter 5	in. to 50 ft., Dia.	in. to	ft., Dia.	in. to ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slo		7. Torch cut	9. Drilled holes	11. None (open hole)	
				······	
2. Louvered shutter 4. Key pu	unched 6. Wire wrapped	8. Saw cut	10. Other (specify)		
SCREEN - PERFORATION INTERVAL	From 50 ft. to	120 ft.,	From ft.	to ft.	
	From ft. to	ft.,	From ft.	to ft.	
GRAVEL PACK INTERVALS:	From 24 ft. to	120 ft.	From ft.	to ft.	
		,	_		
	From ft. to	ft.,	From ft.	to ft.	
6 GROUT MATERIALS: 1. Neat	cement 2. Cement Grout	3. Bentonite	Other bent	tonite hole plug	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible co	7 Pit prive 10). Livestock pens	13. Insecticide storage	15. Oil well/Gas well	
1. Septic tank 4. Lateral lines 4.					
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)					
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? South			How many feet? 30	ft. plus	
From To	LITHOLOGIC LOG	From To	LITHOLO	DGIC LOG	
0 3 topsoil					
3 8 clay					
8 120 grey shale					
			· · · · · · · · · · · · · · · · · · ·		
		<u> </u>		· · · · · ·	
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and					
was completed on (mo/day/year) 7/12/16 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/13/16					
under the business name of Harp Well and Pump Service by (signature) Todd S. Havp					